

USB-C™ Pro Docking Station 17 Port


CDS-17



1x USB-C
4x USB-A



8K
Triple video output
3x HDMI and 2x DP



RJ45 Ethernet Port



SD & MicroSD Slots

Connect. Collaborate. Unleash your productivity.

The Verbatim CDS-17 is a professional docking station with 17 ports.

The versatile hub simplifies device management, accommodates various peripherals, and enhances productivity, making it an ideal solution for users seeking a comprehensive and efficient docking experience for their laptops or workstations, particularly in graphics-intensive or data-intensive tasks.

The CDS-17 possesses one USB-C 3.2 Gen2 and four USB-A ports, ideal for devices like mouse, keyboard, etc. The RJ45 port ensures stable network connectivity, while the SD/MicroSD slots cater to versatile memory card needs.

USB-C™ Pro Docking Station 17 Port

CDS-17

General Information

Product dimensions LxWxD	180 x 100 x 41 mm
Product weight	998
Material	Aluminum+ABS
Colour	Black/Grey

Connection

Host Port	USB-C Host to connect to your device.
Power IN	DC Power port.
USB Ports	1 x USB-A 2.0: up to 480Mb/s - Design for the connection of 2.4 GHz wireless devices, such as wireless keyboards/mouse adapters etc. 2 x USB-A 3.2 Gen1: up to 5Gb/s backwards compatible with USB 2.0. 1 x USB-A 3.2 Gen2: up to 10Gb/s backwards compatible with USB 3.2 Gen1 and USB 2.0. 1 x USB-C 3.2 Gen2: up to 10Gb/s USB-C and USB-A: Power: 5V 0.9A
Video*	1 x HDMI: 8K/30Hz, 4K/60Hz/10bit, 1080p/60Hz/48bit, 720p/60Hz/48bit Bandwidth: Max 12G per Lan 2 x HDMI: 4K/60Hz/10bit, 1080p/60Hz/48bit, 720p/60Hz/48bit Bandwidth: Max 6G per Lan 2 x DP 1.4: 4K/60Hz/10bit, 1080p/60Hz/48bit, 720p/60Hz/48bit. Supports 1080p/720p - Bandwidth: Max 5.4G per Lan HDMI and DP: Support 1080p/720p Support SST (Single-Stream Transport) & MST (Multi-Stream Transport). This Docking Station uses a DisplayLink Chip, you need to install the "DisplayLink Manager" App to experience the full video function. Download the latest "DisplayLink Manager" App: https://www.synaptics.com/products/displaylink-graphics/downloads Please choose the App according to your system, available for Windows, MacOS, Android, Chrome OS and Ubuntu.
Audio	1 x Audio jack 3.5mm: in/out /8 channel sampling rate 192khz/16bit
Memory Card	1 x SD 4.0: Read speed: Up to 250MB/s, Write speed: Up to 250MB/s 1 x Micro SD 3.0 Read speed: Up to 104MB/s, Write speed: Up to 80MB/s
Ethernet	1 x RJ45, up to 1Gb/s

Other Features

Supported OS	Windows 11, 10; MacOS 10.2 or higher
Status LED	Yes
Power Switch	Yes
Power Supply	DC 120W power adapter
DC output	Max. 20V6A 120W and provide 100W power delivery to PC
Safety Lock	Kensington Security Lock Slot

Storage and Operating Conditions

Operating Temperature	0°C to 40°C (32°F to 104°F)
Operating Humidity	20%-90%RH
Storage Temperature	-20°C to 85°C (-4°F to 185°F)
Storage Humidity	5%-95%RH


USB-C™ Pro Docking Station 17 Port

CDS-17

PN	Description	Bar Code	EAN128 Code	EAN14 Code
32172	USB-C Pro Docking Station 17 Port CDS-17	023942321729	(02)0023942321729(37)05(91)892	50023942321724

Logistic Information

Pack Dimensions L x W x H	243 x 175 x 66 mm
Pack Weight	1217
Units per Pack	1
Outer Carton Dimensions L x W x H	350 x 260 x 200 mm
Outer Cartons Weight	6590
Units per Outer Carton	5
Outer Cartons per Layer	9
Layers per Pallet	5
Outer Boxes per pallet	45
Units per Pallet	225



USB-C™ Pro Docking Station 17 Port

CDS-17



Front Angled



Back Angled



Top Angled



Connections



Angle Lit



Angle Lit 2



47454 Packaging 3D



47454 Packaging Flat



Lifestyle 1



Lifestyle 2



Lifestyle 5



Lifestyle 4

Pack Contents:

- USB-C Pro Docking Station
- USB-C to USB-C Cable
- DC Power Supply
- Quick Start Guide

System Requirements

- USB-C host port
- Windows 11, 10 or higher or Mac OS X 10.2 or higher

Warranty

- 2 year limited warranty