

ULTRA-VITALUX

Ultraviolet high-pressure lamps with E27 base



Areas of application


- Sunlight simulation
- Glue curing
- Artificial material aging
- Exposure of UV-sensitive photoresist coatings
- Terrariums
- Equine solaria

Product features

- UV lamp for technical applications
- Direct operation without control gear



Product family datasheet



Product line drawing

Product family datasheet

Technical data

	Electrical data	Photometrical data		Dimensions & weight		Lifespan	Additional product data	Capabilities
Product description	Nominal voltage	Radiated power 315...400 nm (UVA)	Radiated power 280...315 nm (UVB)	Diameter	Length	Lifespan	Base (standard designation)	Burning position
ULTRA VITALUX 300 W 230 V E27	230 V	13.6 W	3.0 W	127.0 mm	185.0 mm	1000 h	E27	Any

Product family datasheet

Safety advice

Due to their intense heat generation, the lamps may only be operated in suitable luminaires. The lamps must also be protected against moisture and splashing water. In case of improper use, UV radiation may lead to sunburn and conjunctivitis. Not approved for use on persons according to the new edition of EN 60335-2-27.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.