


128831 USB 2.0 Cable, USB-C Male to USB-A Male, 0.5m

Product Images





Short Description

- **Connector A:** USB-C Male
- **Connector B:** USB-A Male
- **USB standard:** USB 2.0
- **Data transfer rate:** Up to 480 Mbps
- **Charging current:** Up to 3A
- **Shielding:** Double shielding for stable transmission
- **Connector plating:** Nickel plated
- **Jacket:** PVC
- **Length:** 0.5 m
- **Function:** Charging & data sync

Description

The 128831 USB 2.0 USB-C to USB-A cable provides a reliable solution for charging and data synchronization between USB-C devices and standard USB-A ports.

With support for data transfer speeds of up to 480 Mbps, this cable is suitable for everyday connections to laptops, USB hubs, printers, scanners, and other USB peripherals. Double shielding helps minimize signal interference and ensures stable, error-free data transmission.

Supporting up to 3A output current, the cable enables efficient charging for USB-C smartphones, tablets, and accessories. Nickel-plated connectors and a durable PVC jacket contribute to consistent performance and long-term durability.

Additional Information

Angled Plug.	No
Shielded.	No
Connector 1.	USB-A, male
Connector 2.	USB-C, male
Approval and Compliance.	ROHS, REACH
Color.	Black
Model Number.	128831
Cable Length.	0.5m
Dimensions (W x D x H).	4.5 x 4.5 x 500 mm
Product weight (kg).	0.025
Conductor material.	Copper
Data Rate.	480Mbps
Standards.	USB 2.0

