

Cabinets - Free Standing Network Cabinets



				
Part number (example)		DN-19 42U-8/8-V	DN-19 42U-8/8-1	DN-19 42U-8/8-D
Series		varioFLEX	Unique	Dynamic Basic
Standard sizes	Height units (U)	42U	22U, 26U, 32U, 36U, 42U, 47U	22U, 26U, 32U, 36U, 42U, 47U
	Width (mm)	800	600, 800	600, 800
	Depth (mm)	800	600, 800, 1000, 1200	600, 800, 1000, 1200
Shipping style	Shipping style	Mounted	Mounted	Mounted
Front door	Style (800 mm width cabinets)	Complete steel frame with safety glass, single opening	Complete steel frame with safety glass, single opening	Lateral steel struts with safety glass, single opening
	Style (600 mm width cabinets)	Lateral steel struts with safety glass, single opening	Lateral steel struts with safety glass, single opening	Lateral steel struts with safety glass, single opening
	Locking	Pivot lever with lock, ready for profile-half cylinder (adapter included)	Pivot lever with lock, ready for profile-half cylinder (adapter included)	Pivot lever with lock
	Opening angle	270°	120°	120°
Rear door	Style (800 mm width cabinets)	Steel door, double opening	Steel door with cable entry brushes, double opening	Steel panel, single piece
	Style (600 mm width cabinets)	Steel door, single opening	Steel door with cable entry brushes, single opening	Steel panel, single piece
	Locking	Pivot lever with lock, ready for profile-half cylinder (adapter included)	Lock	Lock
	Opening angle	270°	120°	⊗
Side panels	Side panels	Detachable with snap-in latches, lockable	Detachable with snap-in latches, lockable	Detachable, lockable
Fan area in roof	Fan area in roof	482.6 mm (19") blind panels for individual use	Special construction for fan unit installation	Punched-out holes
	Fan area cover	482.6 mm (19") blind panels for individual use	Top cover (lid) which can be unmounted	⊗
Vertical cable ducts	Vertical cable ducts	Installed in front (left & right)	Installed in front (left & right)	⊗
Cable entry in base	Style (800 mm + 600 mm width cabinets)	482.6 mm (19") blind panels for individual use	Cut-out with sliding cover	Cut-out with screwed cover
	Style (800 mm width cabinets)	Additional cable entry brushes left & right	Additional cable entry brushes left & right	Additional punched out cable entries with plastic covers left & right
Cable entry in top	Style (800 mm + 600 mm width cabinets)	482.6 mm (19") blind panels for individual use	⊗	⊗
	Style (800 mm width cabinets)	Additional cable entry brushes left & right	Cable entry brushes left & right	Punched out cable entries with plastic covers left & right
Load capacity of 19" rails	Load capacity of 19" rails	1200 kg	800 kg	600 kg