

# Cabinets - Free Standing Network Cabinets



|                            |                                        |                                                                                   |                                                                                     |                                                                                     |
|----------------------------|----------------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|                            |                                        |  |  |  |
| Part number (example)      |                                        | DN-19 42U-8/8-V                                                                   | DN-19 42U-8/8-1                                                                     | DN-19 42U-8/8-D                                                                     |
| Series                     |                                        | varioFLEX                                                                         | Unique                                                                              | Dynamic Basic                                                                       |
| Standard sizes             | Height units (U)                       | 42U                                                                               | 22U, 26U, 32U, 36U, 42U, 47U                                                        | 22U, 26U, 32U, 36U, 42U, 47U                                                        |
|                            | Width (mm)                             | 800                                                                               | 600, 800                                                                            | 600, 800                                                                            |
|                            | Depth (mm)                             | 800                                                                               | 600, 800, 1000, 1200                                                                | 600, 800, 1000, 1200                                                                |
| Shipping style             | Shipping style                         | Mounted                                                                           | Mounted                                                                             | Mounted                                                                             |
| Front door                 | Style (800 mm width cabinets)          | Complete steel frame with safety glass, single opening                            | Complete steel frame with safety glass, single opening                              | Lateral steel struts with safety glass, single opening                              |
|                            | Style (600 mm width cabinets)          | Lateral steel struts with safety glass, single opening                            | Lateral steel struts with safety glass, single opening                              | Lateral steel struts with safety glass, single opening                              |
|                            | Locking                                | Pivot lever with lock,<br>ready for profile-half cylinder (adapter included)      | Pivot lever with lock,<br>ready for profile-half cylinder (adapter included)        | Pivot lever with lock                                                               |
|                            | Opening angle                          | 270°                                                                              | 120°                                                                                | 120°                                                                                |
| Rear door                  | Style (800 mm width cabinets)          | Steel door, double opening                                                        | Steel door with cable entry brushes, double opening                                 | Steel panel, single piece                                                           |
|                            | Style (600 mm width cabinets)          | Steel door, single opening                                                        | Steel door with cable entry brushes, single opening                                 | Steel panel, single piece                                                           |
|                            | Locking                                | Pivot lever with lock,<br>ready for profile-half cylinder (adapter included)      | Lock                                                                                | Lock                                                                                |
|                            | Opening angle                          | 270°                                                                              | 120°                                                                                | ⊗                                                                                   |
| Side panels                | Side panels                            | Detachable with snap-in latches, lockable                                         | Detachable with snap-in latches, lockable                                           | Detachable, lockable                                                                |
| Fan area in roof           | Fan area in roof                       | 482.6 mm (19") blind panels for individual use                                    | Special construction for fan unit installation                                      | Punched-out holes                                                                   |
|                            | Fan area cover                         | 482.6 mm (19") blind panels for individual use                                    | Top cover (lid) which can be unmounted                                              | ⊗                                                                                   |
| Vertical cable ducts       | Vertical cable ducts                   | Installed in front (left & right)                                                 | Installed in front (left & right)                                                   | ⊗                                                                                   |
| Cable entry in base        | Style (800 mm + 600 mm width cabinets) | 482.6 mm (19") blind panels for individual use                                    | Cut-out with sliding cover                                                          | Cut-out with screwed cover                                                          |
|                            | Style (800 mm width cabinets)          | Additional cable entry brushes left & right                                       | Additional cable entry brushes left & right                                         | Additional punched out cable entries<br>with plastic covers left & right            |
| Cable entry in top         | Style (800 mm + 600 mm width cabinets) | 482.6 mm (19") blind panels for individual use                                    | ⊗                                                                                   | ⊗                                                                                   |
|                            | Style (800 mm width cabinets)          | Additional cable entry brushes left & right                                       | Cable entry brushes left & right                                                    | Punched out cable entries with plastic covers left & right                          |
| Load capacity of 19" rails | Load capacity of 19" rails             | 1200 kg                                                                           | 800 kg                                                                              | 600 kg                                                                              |