

DIGITUS 4K HDMI Adapter - HDMI to DisplayPort

AK-330101-002-S
EAN 4016032481102



HDMI M to DP F with external Power 4K@30Hz. 0,2 m, black

"With the DIGITUS 4K HDMI Adapter - HDMI to DisplayPort, you can connect your notebook with a second monitor to give you a second screen for more efficient work. Documents, tables and websites can be displayed on multiple screens. The adapter cable supports resolutions up to 4K at 30 Hz. Enjoy sharp image quality with richer colors and considerably more detail than conventional HDs. The adapter transfers Ultra HD content to your DisplayPort monitor and supports 7.1 channel surround audio. The HDMI source can supply this product with sufficient power under most circumstances, the USB-A connection is only connected if not enough power is available"

"With this digital HD high-performance audio/video adapter, connect your HDMI output device to your DP input device."

- Supports: Resolutions up to 4K@30Hz.
- Supports: Resolutions up to 2K@30Hz.
- Supports: Resolutions up to 1920 x 1080 @ 120 Hz.
- Supports: 7.1 channel surround audio.
- Supported color depth: 48 Bit Deep Color
- Supports: 3D video timings
- Supports: eDP operation
- Supports: Video Convert - RGB / YCC (4:4:4) => 16-bit color
- Supports: Color conversion - YUV to RGB and from RGB to YUV
- Compatible with HDMI 1.4 and DisplayPort 1.2
- Compatible with HDCP 1.4 and DPCP
- Connection 1: HDMI Type A (plug)

- Connection 2: DisplayPort (plug)
- Connection 3: USB A (power supply)(plug)
- Length: 0.2 m
- Color: Black
- AOC - Active Optic Cable: No
- Tensile strength: 4 kg/min
- AWG: 30
- Bending radius: 60
- Cable color: black
- Shielding: double shielding
- USB-C product: no
- Total weight: 45 g
- Manufacturer's notice:
- If you connect a USB-C monitor/TV/projector to a PC equipped with USB Type-C, make sure that your USB-C display supports DisplayPort signal output.
- The video output capabilities depend on your notebook's graphic card and the connected monitor. Some screens also limit the available resolution.
- In order to use a dual 4K output, the USB 4 device must support the PD3.0 protocol
- AOC - Active Optical Cable: no
- AOC - Active Optical Cable: no

Package contents

- 1x 4K HDMI Adapter - HDMI to DisplayPort

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	300	1.14	32.00	50.00	21.00	33,600.00
Packaging Unit Inside	10	0.04	4.00	30.00	20.00	2,400.00
Packaging Unit Single	1	0.00	2.00	23.90	116.00	5,544.80
Net single without Packaging	1	0.04	0.60	21.00	11.50	0.00

More images:

