

DK-1P32-050
EAN 4016032481393



- Type: Straight cable
- Cable length: 5 m
- Usuable length: 5 m

- Charging cable type: 3 x 6 mm² + 1 x 0,75 mm²
- Color: Black
- Jacket: TPU
- Connector: EN 62196-2 type 2
- Rated voltage: 230 V
- Rated power: 7,4 kW
- Rated current: 32 A
- Connection phases: 1
- Operating temperature: -30°C+50°C
- Protection class: IP55 (water-jet protected)

- 1 x Charger Cable
- Quick Installation Guide

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	5	15.95	63.00	38.00	38.00	90,972.00
Packaging Unit Inside	1	3.19	0.00	0.00	0.00	0.00
Packaging Unit Single	1	3.19	35.00	35.00	15.00	18,375.00
Net single without Packaging	1	2.51	0.00	0.00	0.00	0.00

Figure 1: Schematic diagrams of the single phase and car correction. The left diagram, labeled 'Single phase and car correction', shows a circular cross-section of a tooth with a central root canal and four side canals. The root canal is labeled '1' and the side canals are labeled '2', '3', '4', and '5'. The right diagram, labeled 'Single phase and car correction', shows a similar cross-section but with a different arrangement of canals. The root canal is labeled '1' and the side canals are labeled '2', '3', '4', and '5'. Below the diagrams is a table with 6 columns and 1 row, labeled '1' through '6'. The table contains the following data: 1, 2, 3, 4, 5, 6.

1	2	3	4	5	6
1	2	3	4	5	6



