

DIGITUS M.2 NVMe/SATA Docking Station

DA-71547

EAN 4016032490388



NVMe/SATA Docking Station USB3.2 Gen2 type C NVMe and SATA SSD docking

The SSD Docking Station from DIGITUS® can accommodate M.2 SSDs in NVMe or SATA technology with up to 4 TB. Supports NVMe SSDs with B+M Key & M-Key and SATA SSDs with B+M-Key, each in the formats 2242, 2260, 2280 & 22110. Easily extend the storage capacity of numerous USB-C™ devices such as PCs, notebooks, TVs, gaming consoles or routers.

Manage M.2 NVMe and M.2 SATA SSDs using a USB-C™ connection

- 1 x M.2 Slot for NVMe / SATA SSDs (B+M-Key / M-Key)
- Supported formats: 2242, 2260, 2280 & 22110
- Capacity: max. 4 TB
- USB-C™ connections: 1 x Data USB-C™ 3.2 Gen2, 1 x Power jack USB-C™
- Backwards-compatible with USB 3.0 / USB 2.0
- Maximum transfer rate USB-C™: 10 Gbps
- Supports U.A.S.P and T.R.I.M.
- Supports Hot Swap (Plug in and eject during operation)

- LED indicators for hard drive transfer (blue), and power (blue)
- Applications PC, notebook, TV, router or gaming console (with USB-C™ connection)
- Storage formats: NTFS, FAT, FAT32
- Systems: Windows 11/10/8/8.1/7/XP, macOS 10.0 or higher
- Connection cable with 18cm
- Dimensions: W: 6 x D: 6 x H: 1,45cm
- Weight: 40 g
- Material: Aluminium + ABS
- Color: black
- Operating temperature: -40°C ~ 80°C
- Manufacturer's notes: Not all USB-C™ ports support all features of the USB Type-C™ standard. Make sure that the USB-C™ port of your notebook supports DisplayPort Alternate Mode (DP-Alt modes) as well as USB Power Delivery (PD).

Package contents

- 1 x SSD Docking Station
- 1 x Quick start guide

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	100	12.60	24.00	52.00	22.00	27,456.00
Packaging Unit Inside	1	0.13	11.00	9.80	1.70	183.26
Packaging Unit Single	1	0.13	11.00	9.80	1.70	183.26
Net single without Packaging	1	0.04	5.00	5.00	1.50	0.00

More images:

