



Universal-Quattro-Switch-LNB

Digital LNB with 4 legacy outputs

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588083905	black	0000/8390	234 g	200 g	5.70 x 10.10 x 12.80 cm	10.20 x 13.80 x 6.10 cm

TOP FEATURES

For 4 participant

Feed ø 40 mm

F connectors

LTE interference-safe

LOCAL OSCILLATOR

Low band : 9,75 GHz

High band : 10,6 GHz

Accuracy : ± 1 MHz

Temperature drift : ± 2.5 MHz

Phase noise : -85 dBc/Hz @10kHz

LNB CONTROL

Vertical : 10.5 ... 14,5 V

Horizontal : 16 ... 22 V

Band switch : 22 kHz

AMBIENT OPERATING CONDITIONS

Ambient temperature : -40 ... 70 °C

Humidity : 10 ... 95 %

INPUT FREQUENCY RANGE

Low band : 10,7 ... 11,7 GHz

High band : 11,7 ... 12,75 GHz

NOISE FACTOR

Noise figure : typ. 0.75 dB

OUTPUT FREQUENCY RANGE

Low band : 950 ... 1950 MHz

High band : 1100 ... 2150 MHz

POWER SUPPLY

Power consumption : typ. 150 mA

PREPARED FOR

Number of clients : 4

Number of orbit positions : 1

TECHNICAL DATA

Outputs : 4

Impedance : 75 Ω

Feed reception : 40 mm

Connector type : F female

Amplification : 60 ... 65 dB

SCOPE OF DELIVERY

Universal-Quattro-Switch-LNB