

### Product Datasheet uvex 1 sport 6594.1-4 S1 P SRC



**UVEX ARBEITSSCHUTZ GmbH, Würzburger Str. 181-189, D-90766 Fürth**

#### Product information

- Modern, ultralightweight and flexible safety shoe
- 100 % metal-free uvex xenova® toe cap – compact design, anatomical shape, good lateral stability, no thermal conductivity
- Penetration-resistant, non-metallic midsole in accordance with the latest safety standards, does not restrict flexibility of the shoe
- Outstanding wearer comfort results from a newly developed last and climate-optimised, breathable materials
- uvex climazone technology for optimum comfort
- Virtually seam-free construction made from high-tech materials to eliminate pressure points
- Suitable for people allergic to chrome as it's made from synthetic materials
- Removeable anti-static comfortable insole, with a moisture transport system and additional shock absorption around the heel and forefoot
- Soft padding on collar and tongue
- Sizes 35 – 40 have been produced using a women's last
- Meets the ESD specification with leakage resistance less than 35 megaohms

#### Outsole

- Ergonomically designed outsole comprising dual-density polyurethane with excellent slip resistant
- All sole materials are free of silicones, plasticisers and other paint wetting impairment substances

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |          |        |    |    |    |         |    |    |    |    |          |                            |  |  |  |      |         |  |  |  |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|--------|----|----|----|---------|----|----|----|----|----------|----------------------------|--|--|--|------|---------|--|--|--|
|                       | <ul style="list-style-type: none"><li>Withstands brief exposure to heat of approx. +120°C</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                |          |        |    |    |    |         |    |    |    |    |          |                            |  |  |  |      |         |  |  |  |
| <b>Technical Data</b> | <table><tr><td>Art.-no.</td><td>6594.1</td><td>.2</td><td>.3</td><td>.4</td></tr><tr><td>Fitting</td><td>10</td><td>11</td><td>12</td><td>14</td></tr><tr><td>Standard</td><td colspan="4">EN ISO 20345:2011 S1 P SRC</td></tr><tr><td>Size</td><td colspan="4">35 – 52</td></tr></table>                                                                                                                                                                                                                                          | Art.-no. | 6594.1 | .2 | .3 | .4 | Fitting | 10 | 11 | 12 | 14 | Standard | EN ISO 20345:2011 S1 P SRC |  |  |  | Size | 35 – 52 |  |  |  |
| Art.-no.              | 6594.1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | .2       | .3     | .4 |    |    |         |    |    |    |    |          |                            |  |  |  |      |         |  |  |  |
| Fitting               | 10                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 11       | 12     | 14 |    |    |         |    |    |    |    |          |                            |  |  |  |      |         |  |  |  |
| Standard              | EN ISO 20345:2011 S1 P SRC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |          |        |    |    |    |         |    |    |    |    |          |                            |  |  |  |      |         |  |  |  |
| Size                  | 35 – 52                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |          |        |    |    |    |         |    |    |    |    |          |                            |  |  |  |      |         |  |  |  |
| <b>Accessories</b>    | <p><i>removeable uvex 1 sport climatic insole</i><br/>(article no.: 9579.7/.8/.9/.0)</p> <ul style="list-style-type: none"><li>Provides the foot with exceptional, full-surface shock absorption and ensures comfort in high-strain zones</li><li>Ultra-breathable and moisture-absorbing materials</li><li>Shock absorption zones that assist natural movement</li><li>Non-irritating, comfortable surface structure</li></ul> <p><i>Laces</i></p> <ul style="list-style-type: none"><li>Black (article no.: 8446.0 10)</li></ul> |          |        |    |    |    |         |    |    |    |    |          |                            |  |  |  |      |         |  |  |  |