

## Product Datasheet uvex 2 xenova 9569 1 -3 S3 SRC

**UVEX ARBEITSSCHUTZ GmbH, Würzburger Str. 181-189, D-90766 Fürth**

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                     |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>General features</b>    | <ul style="list-style-type: none"><li>• Ultra low weight and versatile S3 safety boot</li><li>• upper: water-repellent, full-grain smooth leather</li><li>• All sole materials are free of silicones, plasticisers and other paint wetting impairment substances</li><li>• Heat-resistant lace loop system</li><li>• BOA® Fit System for a fast, effortless, precision fit</li></ul>                                |
| <b>Protection features</b> | <ul style="list-style-type: none"><li>• Meets ESD requirements: resistance to ground &lt; 35 megaohm</li><li>• 100% metal-free uvex xenova® toe cap. Compact design, anatomical shape, good lateral stability, no thermal conductivity properties</li><li>• Ergonomically designed outsole made from dual density polyurethane with excellent slip resistance</li></ul>                                             |
| <b>Comfort features</b>    | <ul style="list-style-type: none"><li>• Light weight and optimised shock absorption<br/>Outstanding wearer comfort results from a newly developed last and climate-optimised, breathable materials</li><li>• Removable comfort insole, antistatic, with moisture control system and additional shock absorption in the heel and at the front of the foot</li><li>• Soft padding on collar and dust tongue</li></ul> |
| <b>Outsole</b>             | <ul style="list-style-type: none"><li>• PUR outsole, non-marking</li><li>• Ergonomically designed tread</li><li>• Extremely flexible, excellent shock absorption</li></ul>                                                                                                                                                                                                                                          |

|                      |                                                                                                                                                                                                                                                                                                                                                                                                                      |          |        |    |    |       |    |    |    |          |                          |  |  |      |         |  |  |
|----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|--------|----|----|-------|----|----|----|----------|--------------------------|--|--|------|---------|--|--|
|                      | <ul style="list-style-type: none"><li>• Unique PUR outsole system makes the shoe ultra-light</li><li>• Two-layer system with abrasion-resistant and cut-resistant outsole</li><li>• Excellent slip resistance</li><li>• Self-cleaning tread</li><li>• Resistant to oil and petrol</li><li>• Resistant to temperatures for short periods up to ca. +120°C</li></ul>                                                   |          |        |    |    |       |    |    |    |          |                          |  |  |      |         |  |  |
| Certificates         | <ul style="list-style-type: none"><li>• Certified with uvex medicare for individual, orthopaedic inlay soles and individual adjustments of the sole unit such as overall increase, inside and outside increase and other solutions.</li></ul>                                                                                                                                                                        |          |        |    |    |       |    |    |    |          |                          |  |  |      |         |  |  |
| Areas of application | <ul style="list-style-type: none"><li>• Moderate applications</li></ul>                                                                                                                                                                                                                                                                                                                                              |          |        |    |    |       |    |    |    |          |                          |  |  |      |         |  |  |
| Technical data       | <table><tr><td>Art.-no.</td><td>9569.1</td><td>.2</td><td>.3</td></tr><tr><td>Width</td><td>10</td><td>11</td><td>12</td></tr><tr><td>Standard</td><td colspan="3">EN ISO 20345:2011 S3 SRC</td></tr><tr><td>Size</td><td colspan="3">38 – 52</td></tr></table>                                                                                                                                                      | Art.-no. | 9569.1 | .2 | .3 | Width | 10 | 11 | 12 | Standard | EN ISO 20345:2011 S3 SRC |  |  | Size | 38 – 52 |  |  |
| Art.-no.             | 9569.1                                                                                                                                                                                                                                                                                                                                                                                                               | .2       | .3     |    |    |       |    |    |    |          |                          |  |  |      |         |  |  |
| Width                | 10                                                                                                                                                                                                                                                                                                                                                                                                                   | 11       | 12     |    |    |       |    |    |    |          |                          |  |  |      |         |  |  |
| Standard             | EN ISO 20345:2011 S3 SRC                                                                                                                                                                                                                                                                                                                                                                                             |          |        |    |    |       |    |    |    |          |                          |  |  |      |         |  |  |
| Size                 | 38 – 52                                                                                                                                                                                                                                                                                                                                                                                                              |          |        |    |    |       |    |    |    |          |                          |  |  |      |         |  |  |
| Accessories          | <p><i>comfortable climatic insole</i><br/>(Article-no.: 9534.7-9)</p> <ul style="list-style-type: none"><li>• Provides the foot with exceptional, full-surface shock absorption and ensures comfort in high-strain zones</li><li>• Ultra breathable and moisture-absorbing materials</li><li>• Shock absorption zones that assist natural movement</li><li>• Non-irritating, comfortable surface structure</li></ul> |          |        |    |    |       |    |    |    |          |                          |  |  |      |         |  |  |