

# USB Mono Headset with Volume Control for PC and Laptop - Ultra Lightweight

## Description

This USB headset by Delock is suitable for playback and recording of audio signals which can be used for working at home or for small business usage. It is ideally suited for **Skype, video conferencing** or **online-courses**.

### Optimal recordings & good sound

Due to the flexible microphone arm, the microphone picks up voice and vocal transmissions loud and clear. The **270° adjustable microphone arm** allows the microphone to be used on the right or left side.

The headset offers a sampling rate of up to **16 Bit / 48 kHz** and can therefore record and playback audio signals in **DVD quality**.

### Comfortable to wear

The headset has foam earmuff and is **ultra-light** at only about **70 grams**. The headband can be adjusted to the required head size. Therefore the headset offers a pleasant wearing comfort even during longer use.

### Stepless volume control

The cable has a volume control, which can be used to adjust the volume on the headset as required.

### Plug & Play

Due to USB Plug & Play the headset is ready to use immediately and no driver installation is necessary. The headset works with all common operating systems such as **Windows, Mac OS, Chrome OS** and **Linux**.



## Specification

- Connector: 1 x USB 2.0 Type-A male
- Directivity: omnidirectional
- Sensitivity:
  - Headphone: 105 dB +/- 3 dB
  - Microphone: -42 dB +/- 2 dBV/Pa
- Frequency range:
  - Headphone: 20 Hz - 20 kHz
  - Microphone: 40 Hz - 13 kHz
- Impedance: 32 +/- 5 Ohm
- Sample rate: 16 Bit / 48 kHz for record and playback
- Volume control (loud / quiet)
- Cable length: ca. 2.4 m
- Weight: ca. 70 g
- USB bus powered
- Plug & Play

## System requirements

- Chrome OS
- Linux Kernel 5.4 or above
- Mac OS 10.9 or above
- Windows 8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

## Package content

- USB headset
- Windscreen

## Item no. 27177

EAN: 4043619271771

Country of origin: China

Package: Retail Box



- User manual

## Images





| General                     |                                                                                                                                                                                              |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Function:                   | Plug & Play                                                                                                                                                                                  |
| Specification:              | USB 2.0                                                                                                                                                                                      |
| Supported operating system: | Chrome OS<br>Linux Kernel 5.4 or above<br>Mac OS 10.9 or above<br>Windows 10 32-bit<br>Windows 10 64-bit<br>Windows 8 32-bit<br>Windows 8 64-bit<br>Windows 8.1 32-bit<br>Windows 8.1 64-bit |
| Style:                      | Mono                                                                                                                                                                                         |
| Interface                   |                                                                                                                                                                                              |
| connector:                  | 1 x USB 2.0 Type-A male                                                                                                                                                                      |
| Technical characteristics   |                                                                                                                                                                                              |
| Frequency range:            | 20 Hz - 20 kHz<br>40 Hz - 13 kHz                                                                                                                                                             |
| Impedance:                  | 32 +/- 5 Ohm                                                                                                                                                                                 |
| Voltage:                    | USB bus powered                                                                                                                                                                              |
| Sensibility:                | 105 dB +/- 3 dB<br>-42 dB +/- 2 dBV/Pa                                                                                                                                                       |
| Sample rate:                | 16 Bit / 48 kHz                                                                                                                                                                              |
| Directivity:                | omnidirectional                                                                                                                                                                              |
| Physical characteristics    |                                                                                                                                                                                              |
| Weight:                     | 70 g                                                                                                                                                                                         |
| Cable colour:               | black                                                                                                                                                                                        |
| Cable length:               | 2.4 m                                                                                                                                                                                        |