

# Delock USB Adapter 40 Gbps USB Type-C™ PD 3.1 240 W male to female angled left / right 8K 60 Hz

## Description

This USB-C™ adapter by Delock can be used for the connection of USB-C™ devices. It can be also connected to a free USB-C™ port in order to prevent the interface from damage when it is under usage for high contact durability.



**Item no. 60245**

EAN: 4043619602452

Country of origin: China

Package: Zip poly bag

## Specification

- Connectors:
  - 1 x USB 40 Gbps USB Type-C™ male
  - 1 x USB 40 Gbps USB Type-C™ female
- Data transfer rate up to 40 Gbps
- USB Power Delivery (USB PD 3.1) support up to 240 watt
- Output current: up to 5 A
- Voltage: max. 48 V
- Supports DP Alt Mode
- Maximum resolution (depending on the system and the connected hardware):
  - DisplayPort 1.4 with DSC: up to 7680 x 4320 @ 60Hz
  - DisplayPort 1.4 with DSC: up to 3840 x 2160 @ 144 Hz
- Transmission of audio and video signals
- HDCP and HDR support
- Downwards compatible to USB 3.2, USB 2.0 and Thunderbolt™ 3, Thunderbolt™ 4
- Useable on both sides
- Housing material: PVC
- Colour: anthracite
- Dimensions (LxWxH): ca. 2.7 x 1.2 x 0.7 cm

---

## Package content

- USB adapter

## General

|                |                     |
|----------------|---------------------|
| Specification: | USB Type-C™<br>USB4 |
|----------------|---------------------|

## Interface

|              |                        |
|--------------|------------------------|
| Connector 1: | 1 x USB Type-C™ male   |
| Connector 2: | 1 x USB Type-C™ female |

## Technical characteristics

|                     |         |
|---------------------|---------|
| Operating voltage:  | 48 V    |
| Data transfer rate: | 40 Gbps |

## Physical characteristics

|                   |        |
|-------------------|--------|
| Housing material: | PVC    |
| Length:           | 2.7 cm |
| Width:            | 1.2 cm |
| Height:           | 0.7 cm |
| Colour:           | black  |