

# Delock S/PDIF TOSLINK Splitter 1 In 3 Out with USB Powered

## Description

With this TOSLINK splitter by Delock up to three TOSLINK devices can be operated at the same time at one TOSLINK output.

### Supports HD audio formats

The splitter supports all popular **2.0** and **5.1** audio formats such as **LPCM**, **Dolby Digital**, **DTS Audio** and therefore offers a sound experience like in a cinema.

### High resolution sampling rate

The splitter offers a sampling rate of up to **24 bit** and **96 kHz**. This allows a loss-free playback of the sound in the High-Res audio range.

### High transmission distance

The splitter supports an output transmission distance of up to **40 m** via an optical TOSLINK cable with a signal loss of less than 0.2 dB / m.

### USB powered

The splitter does not require an additional external power supply, power will be supplied via the included USB cable.



**Item no. 63397**

EAN: 4043619633975

Country of origin: China

Package: Retail Box

## Technical details

- Connectors:  
Input:  
1 x TOSLINK female S/PDIF  
1 x USB Type Mini-B female (5 V power supply)  
Output: 3 x TOSLINK female S/PDIF
- Supported sample rates: 32 / 44.1 / 48 / 96 kHz
- Bit rate 16 - 24 Bit
- Baud rate: max. 16 Mbps
- Supports all common 2.0 and 5.1 audio formats: LPCM, Dolby Digital, DTS Audio
- Supports signal retiming
- On / Off switch

- Power LED (blue)
- Plastic housing
- Colour: black
- Dimensions (LxWxH): ca. 61 x 54 x 20 mm
- Voltage: 5 V
- Surge Protection
- USB bus powered

## System requirements

- Digital optical audio signal
- A free USB Type-A female port

## Package content

- TOSLINK splitter
- USB Type-A to Type Mini-B cable, length ca. 75 cm
- User manual

## Images



## General

|                |                                    |
|----------------|------------------------------------|
| Specification: | DTS Audio<br>Dolby Digital<br>LPCM |
| LED indicator: | Power                              |

## Interface

|         |                                                                             |
|---------|-----------------------------------------------------------------------------|
| Output: | 3 x TOSLINK female S/PDIF                                                   |
| Input:  | 1 x TOSLINK female S/PDIF<br>1 x USB Type Micro-B female (5 V power supply) |

## Technical characteristics

|                     |                         |
|---------------------|-------------------------|
| Bit rate:           | 16 - 24 Bit             |
| Data transfer rate: | max. 16 Mbps            |
| Voltage:            | USB bus powered         |
| Sample rate:        | 32 / 44,1 / 48 / 96 kHz |

## Physical characteristics

|                 |       |
|-----------------|-------|
| Housing colour: | black |
| Length:         | 61 mm |
| Width:          | 54 mm |
| Height:         | 20 mm |
| LED colour:     | blue  |