



# Delock 10" Industry Hub 10 x USB 3.2 Gen 1 Type-A

## Description

This solid industry capable USB hub by Delock with metal housing can be connected to a computer via the USB Type-A interface. It expands the computer by 10 USB Type-A ports. The hub can be used for automation and office applications.

## USB 3.2 Gen 1 specification

With the support of USB 3.2 Gen 1 specification a data transfer rate up to 5 Gbps can be reached. Compared to USB 2.0, data can be transferred 10 times faster. All ports are backward compatible, so USB 2.0 and USB 1.1 devices can be used as well.

## 10" rack mounting

With the supplied mounting brackets, the hub can be mounted in a 10" rack.



## Specification

- Connectors:
  - 1 x SuperSpeed USB (USB 3.2 Gen 1) Type-B female
  - 10 x SuperSpeed USB (USB 3.2 Gen 1) Type-A female
  - 1 x 5 V DC jack 5.5 x 2.1 mm
- Chipset: VIA VL813
- Data transfer rate up to:
  - SuperSpeed USB 5 Gbps,
  - Hi-Speed 480 Mbps,
  - Full-Speed 12 Mbps,
  - Low-Speed 1.5 Mbps
- Output power: max. 16 W total
- Robust metal housing
- Removable 10" rack brackets
- LED indicator for power
- Operating temperature: 0 °C ~ 60 °C
- Dimensions (LxWxH): ca. 215 x 135 x 45 mm
- Colour: black
- Plug & Play

## Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 1.0 A
- Output: 5 V / 4 A
- Ground outside, plus inside
- Dimensions:
  - inside: ø ca. 2.1 mm
  - outside: ø ca. 5.5 mm
  - length: ca. 9 mm

## System requirements

- Linux Kernel 3.4 or above
- Windows 8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

## Package content

- Hub USB
- 1 x cable USB 3.2 Gen 1 Type-A male to USB 3.2 Gen 1 Type-B male, length ca. 1.20 m
- 2 x mounting brackets for 10" rack
- Power supply
- User manual

## Item no. 64112

EAN: 4043619641123

Country of origin: China

Package: • Box



Images





| General                     |                            |
|-----------------------------|----------------------------|
| Function:                   | Hot Swap                   |
|                             | Plug & Play                |
| Mounting type:              | 10 in                      |
| Supported operating system: | Chrome OS                  |
|                             | Linux Kernel 3.3 or above  |
|                             | Windows 10 64-bit          |
|                             | Windows 7 64-bit           |
|                             | Windows 8.1 64-bit         |
| LED indicator:              | Power                      |
| Interface                   |                            |
| Connector 1:                | 1 x USB 3.0 Type-B female  |
| Connector 2:                | 10 x USB 3.0 Type-A female |
| connector 3:                | 1 x DC jack                |
| Technical characteristics   |                            |
| Data transfer rate:         | USB 3.0 up to 5 Gb/s       |
| Physical characteristics    |                            |
| Length:                     | 215 mm                     |
| Width:                      | 135 mm                     |
| Height:                     | 45 mm                      |
| Colour:                     | black                      |
| Power supply                |                            |
| Type:                       | Euro wall power supply     |
| Output:                     | 5 V / 4 A                  |
| Connector:                  | DC male 5.5 mm x 2.1 mm    |