

# Delock Combo Converter for M.2 NVMe PCIe or SATA SSD with USB 3.2 Gen 2

## Description

This converter by Delock enables the installation of an **M.2 PCIe NVMe SSD or SATA M.2 SSD** in **2280, 2260, 2242 and 2230** format, it can be connected via USB to the PC or laptop.

### Combo converter

The big advantage of this Delock M.2 converter is that both SATA and PCIe (NVMe) M.2 SSDs can be inserted into the converter. The **memory is automatically recognized by the chipset** and can then be used.

### Ideal test equipment

Due to the USB-A connector and the **direct installation of the SSD** on the board, without enclosure, the Delock converter is most suitable as test equipment.



**Item no. 64197**

EAN: 4043619641970

Country of origin: China

Package: Retail Box

## Technical details

- Connectors:
  - 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) Type-A male
  - 1 x 67 pin M.2 key M slot
- Chipset: Realtek RTL9210B
- Supports M.2 modules in format 2280, 2260, 2242 and 2230 with key M or key B+M based on SATA or PCIe (NVMe)
- Supports NVM Express (NVMe)
- Data transfer rate up to 10 Gbps
- LED indicator for power and access
- Bootable
- Dimensions (LxWxH): ca. 110 x 22 x 6 mm
- Plug & Play

## System requirements

- Android 11.0 or above
- Chrome OS
- Linux Kernel 5.13 or above
- Mac OS 12.3.1 or above
- Windows 8.1/8.1-64/10/10-64/11
- PC or laptop with a free USB Type-A port


---

## Package content

- M.2 converter
- Mounting material
- Screwdriver
- User manual

---

## Images



## General

|                                                 |                                                                                                                                                                                                |
|-------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Function:                                       | NVM Express (NVMe)<br>Plug & Play<br>bootable                                                                                                                                                  |
| Supported operating system:                     | Chrome OS<br>Windows 10 32-Bit<br>Windows 10 64-Bit<br>Windows 8.1 32-Bit<br>Windows 8.1 64-Bit<br>Windows 11<br>Linux Kernel 5.13 or above<br>Mac OS 12.3.1 or above<br>Android 11.0 or above |
| LED indicator:                                  | power and activity                                                                                                                                                                             |
| Slot:                                           | PCIe<br>SATA                                                                                                                                                                                   |
| Supported module:                               | M.2 modules in format 2280, 2260, 2242 and 2230 with key M or key B+M based on SATA or PCIe                                                                                                    |
| Maximum height of the components on the module: | 1.5 mm application of double-sided assembled modules supported                                                                                                                                 |

## Interface

|              |                                    |
|--------------|------------------------------------|
| Connector 1: | 1 x USB 10 Gbps Type-A male (host) |
| Connector 2: | 1 x 67 pin M.2 key M slot          |

## Technical characteristics

|                     |                  |
|---------------------|------------------|
| Chipset:            | Realtek RTL9210B |
| Data transfer rate: | 10 Gbps          |