

# Delock 7 Port USB 3.2 Gen 2 Hub with 4 USB Type-A and 3 USB Type-C™ Ports

## Description

The USB hub by Delock can be connected via USB Type-C™ interface to a PC or laptop. It has **four USB Type-A connectors** as well as **three USB Type-C™ connectors**. Different USB devices such as HDD docking station, card reader, external enclosure etc. can be connected.

## Supports SuperSpeed USB 10 Gbps

A maximum data transfer rate of up to USB 3.2 Gen 2 - 10 Gbps can be reached.



**Item no. 64209**

EAN: 4043619642090

Country of origin: China

Package: Retail Box

## Specification

- Connectors:
  - 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ female
  - 4 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) Type-A female
  - 3 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ female
  - 1 x 5 V DC jack
- Data transfer rate up to:
  - SuperSpeed USB 10 Gbps,
  - SuperSpeed USB 5 Gbps,
  - Hi-Speed 480 Mbps,
  - Full-Speed 12 Mbps,
  - Low-Speed 1.5 Mbps
- LED indicator
- Power supply: Self-powered
- Electrical power per port:
  - USB Type-C™: max. 10 watt (5 V / 2 A)
  - USB Type-A: max. 7.5 watt (5 V / 1.5 A)
- Dimensions (LxWxH): ca. 120 x 65 x 12 mm
- Colour: black
- Plug & Play

---

## Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.6 A
- Output: 5 V / 4 A
- Ground outside, plus inside
- Dimensions:
  - inside: ø ca. 2.1 mm
  - outside: ø ca. 5.5 mm
  - length: ca. 10 mm

---

## System requirements

- Mac OS 12.2.1 or above
- Windows 8.1/8.1-64/10/10-64/11
- iPad Air (4th Generation) or above
- iPad Pro (3rd Generation) or above
- Surface Pro 7
- Device with a free USB Type-C™ port or with a free Thunderbolt™ 3 port or
- Device with a free USB4™ port or with a free Thunderbolt™ 4 port

---

## Package content

- Hub USB 3.2 Gen 2
- Cable USB-C™ male to USB-C™ male, length ca. 1 m
- Power supply
- User manual

## Images



## General

|                             |                                                                                                                                                                                                                         |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Supported operating system: | Surface Pro 7<br>Windows 10 32-bit<br>Windows 10 64-bit<br>Windows 8.1 32-bit<br>Windows 8.1 64-bit<br>iPad Pro (3rd Generation) or above<br>iPad Air (4th Generation) or above<br>Windows 11<br>Mac OS 12.2.1 or above |
| LED indicator:              | 1 x                                                                                                                                                                                                                     |

## Interface

|              |                                                               |
|--------------|---------------------------------------------------------------|
| Connector 1: | 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ female |
| Connector 2: | 4 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) Type-A female      |
| connector 3: | 3 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ female |
| connector 4: | 1 x 5 V DC jack                                               |

## Technical characteristics

|                     |         |
|---------------------|---------|
| Data transfer rate: | 10 Gbps |
|---------------------|---------|

## Physical characteristics

|               |         |
|---------------|---------|
| Cable length: | 1 m     |
| Material:     | plastic |
| Length:       | 120 mm  |
| Width:        | 65 mm   |
| Height:       | 12 mm   |
| Colour:       | black   |

## Power supply

|        |                                     |
|--------|-------------------------------------|
| Input: | AC 100 - 240 V / 50 - 60 Hz / 0.6 A |
|--------|-------------------------------------|

|            |                         |
|------------|-------------------------|
| Output:    | 5 V / 4 A               |
| Connector: | DC male 5.5 mm x 2.1 mm |