




Delock Adapter cable USB Type-A to Serial RS-232 RJ12 with ESD protection Skywatcher 2 m

Description

This USB to RS-232 RJ12 adapter cable by Delock is suitable for the PC operation of hand control boxes by the Skywatcher Telescopes. With the appropriate astronomy applications, the position of the telescope can be controlled by the computer or a firmware update can be carried out.

**2 m**

Specification

- Connectors:
 - 1 x USB 2.0 Type-A male
 - 1 x Serial RS-232 RJ12 plug
- Chipset: FTDI FT231X
- Plug & Play
- FIFO: 512 Byte - TX
- FIFO: 512 Byte - RX
- Compatible with USB 3.0, USB 2.0, and USB 1.1 full speed 12 Mbps
- Data transfer rate up to 230.4 Kb/s
- Signals: RXD(2), GND(3), GND(4), TXD(5)
- ESD protection IEC 61000-4-2
- HCP & VCP: ± 4 kV
- Air Discharge: ± 8 kV
- Contact Discharge: ± 4 kV
- Colour: black
- Cable length incl. connectors: ca. 2.0 m
- Suitable for various Skywatcher hand controllers

System requirements

- Windows 8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

Package content

- Adapter cable USB 2.0 Type-A to RS-232 RJ12

Item no. 66735

EAN: 4043619667352

Country of origin: China

Package: • Zip poly bag

Images





General

Specification: RS-232 (EIA / TIA)
USB 2.0

Supported operating system: Windows 8.1 32-bit
Windows 8.1 64-bit
Windows 10 32-bit
Windows 10 64-bit

Interface

Connector 1: 1 x USB 2.0 Type-A male

Connector 2: 1 x RJ12 plug

Technical characteristics

Chipset: FTDI FT231XS

Data transfer rate: bis zu 230,4 Kbps

FIFO: 2 x 512 Byte

Signal transmission: TxD, RxD und GND

UART: USB to serial UART

Physical characteristics

Cable length incl. connector: 2 m

Colour: black

Overvoltage protection: ± 8 kV EN / IEC 61000-4-2 Air Gap Discharge
 ± 4 kV EN / IEC 61000-4-2 Contact Discharge
 ± 4 kV EN / IEC 61000-4-2 VCP & HCP