



Delock Cable HDMI-A female > HDMI-A female panel-mount 4K 30 Hz 0.5 m

Description

This cable by Delock can be used to extend an HDMI connection and to connect various devices. The female port can be attached with two screws, e.g. to a slot bracket, a cable duct or an enclosure with the corresponding opening. In this way, it is possible to install a HDMI connector in an easily accessible position.



ca. 0,5 m

Specification

- Connectors:
 - 1 x HDMI-A 19 pin female >
 - 1 x HDMI-A 19 pin female panel-mount
- High Speed HDMI with Ethernet (HEC) specification
- Screw type: #4-40 UNC
- Mounting hole: ca. 15 x 6 mm, screw hole pitch ca. 30 mm
- Cable gauge: 28 AWG
- Cable diameter: ca. 7.3 mm
- Gold-plated connectors
- Transfer of audio and video signals
- Data transfer rate up to 10.2 Gb/s
- Resolution up to 3840 x 2160 @ 30 Hz (depending on the system and the connected hardware)
- 3D support up to 1080p in two video streams with each 60 pictures per second
- Supports Dolby® TrueHD and DTS-HD Master Audio™
- Colour: black
- Length incl. connectors: ca. 50 cm

System requirements

- A free HDMI interface

Package content


- HDMI panel-mount cable
- 2 screws

Item no. 85465

EAN: 4043619854653

Country of origin: China

Package: Poly bag



Images





General	
Specification:	High Speed HDMI with Ethernet
Interface	
connector 1:	1 x High Speed HDMI-A 19 pin female
connector 2:	1 x High Speed HDMI-A 19 pin female
Technical characteristics	
Data transfer rate:	10.2 Gb/s
Maximum screen resolution:	3840 x 2160 @ 30 Hz
Physical characteristics	
Cable diameter:	7.3 mm
Pin finishing:	gold-plated
Conductor gauge:	28 AWG
Screw distance:	30 mm
Screw type:	#4-40 UNC
Length:	50 cm
Colour:	black