




Delock PoweredUSB Kabel Stecker 12 V > DC 5,5 x 2,1 mm Stecker 2 m für POS Drucker und Terminals

Description

This PoweredUSB cable by Delock can be used to supply power to a device with DC 5.5 x 2.1 mm female port via a PC or hub with PoweredUSB 12 V port.



Specification

- Connectors:
 - 1 x PoweredUSB male 12 V >
 - 1 x DC 5.5 x 2.1 mm male
- PoweredUSB specification
- Voltage: 12 V
- Cable gauge: 24 AWG
- Cable diameter: ca. 6 mm
- Cable double shielded
- Colour: black
- Length incl. connectors (L): ca. 2 m

System requirements

- PC or hub with a free PoweredUSB 12 V female port

Package content

- PoweredUSB cable

Item no. 85498

EAN: 4043619854981

Country of origin: China

Package: Poly bag



Images





General	
Specification:	PoweredUSB
Interface	
Connector 1:	1 x PoweredUSB male 12 V
Connector 2:	1 x DC 5.5 x 2.1 mm male
Technical characteristics	
Voltage:	12 V
Physical characteristics	
Cable diameter:	6 mm
Conductor gauge:	24 AWG power line
Shielding:	double
Length:	2 m
Colour:	black