



2.5 Gigabit Ethernet Switch 8 Port

Description

This 2.5 Gigabit Ethernet Switch by Delock can be used to connect different network components.

NBASE-T for higher speed

Modern services and new technologies require higher bandwidths. NBASE-T technology enables speeds of 1 Gbps and 2.5 Gbps with conventional networking cables. The best possible transmission rate is set automatically.

2.5
GIGABIT LAN

Specification

- Connectors:
 - 8 x 2.5 Gigabit LAN RJ45 jack
 - 1 x DC 5.5 x 2.1 mm female
- Data transfer rate:
 - Ethernet up to 10 Mbps
 - Fast Ethernet up to 100 Mbps
 - Gigabit Ethernet up to 1000 Mbps
 - 2,5 Gigabit Ethernet up to 2500 Mbps
- Supports IEEE 802.3 / 802.3u / 802.3ab / 802.3bz / 802.3x
- Support full duplex operation with IEEE 802.3x flow control and half duplex operation with back-pressure
- Bandwidth: 40 Gbps
- Supports 12k Jumbo Frames
- LED indicator for link and activity
- Reset button
- Robust metal housing
- Security lock (Kensington Lock) for security cable
- Removable wallmount brackets
- Fanless
- Operating temperature: 0 °C ~ 40 °C
- Dimensions (LxWxH): ca. 190 x 120 x 30 mm

Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.6 A
- Output: 12.0 V / 1.8 A / 21.6 W
- Ground outside, plus inside
- Dimensions:
 - inside: ø ca. 2.1 mm
 - outside: ø ca. 5.5 mm

System requirements

- Device with one free RJ45 port

Package content

- Switch
- Wall mounting brackets
- External power supply
- User manual

Item no. 87782

EAN: 4043619877829

Country of origin: China

Package: White Box



Images





General	
Mounting type:	wall
Interface	
Output:	8 x 2.5 Gigabit LAN RJ45 jack
Input:	1 x DC 5.5 x 2.1 mm female
Technical characteristics	
Data transfer rate:	Ethernet up to 10 Mbps
	Fast Ethernet up to 100 Mbps
	Gigabit Ethernet up to 1 Gbps
	Gigabit Ethernet up to 2.5 Gbps
Operating temperature:	0 °C ~ 40 °C
Physical characteristics	
Housing colour:	black
Housing material:	metal
Length:	190 mm
Width:	120 mm
Height:	30 mm