



## Delock Adapter SMA plug to RP-SMA jack 3 GHz

### Description

This adapter by Delock is suitable for connecting components of radio frequency technology.



### Specification

- Connectors:
  - 1 x SMA plug >
  - 1 x RP-SMA jack
- Housing: brass gold plated
- Thread type: 1/4" - 36 UNS - 2A
- Inner thread: 1/4" - 36 UNS - 2B
- Frequency range: 3 GHz
- Impedance: 50 Ohm
- Operating temperature: -10 °C ~ 50 °C
- Dimensions (LxD): ca. 25.6 x 7.0 mm

### System requirements

- Device with one free SMA or RP-SMA port

### Package content

- Adapter

### Item no. 89991

EAN: 4043619899913

Country of origin: Taiwan, Republic of China

Package: Poly bag



|                           |                                                       |
|---------------------------|-------------------------------------------------------|
| Interface                 |                                                       |
| Connector 1:              | <b>standard</b><br>1 x SMA plug                       |
| Connector 2:              | <b>standard</b><br>1 x RP-SMA jack                    |
| Technical characteristics |                                                       |
| Frequency range:          | <b>standard</b><br>3 GHz                              |
| Operating temperature:    | <b>standard</b><br>-10 °C ~ 50 °C                     |
| Physical characteristics  |                                                       |
| Housing material:         | <b>standard</b><br>Brass gold plated                  |
| Diameter:                 | <b>standard</b><br>HEX 8 mm , max. 7 mm               |
| Length:                   | <b>standard</b><br>25.6 mm                            |
| Thread type:              | <b>standard</b><br>1/4" - 36 UNS - 2A<br>1/4 36UNS-2B |