



## Delock Adapter SMA jack to RP-SMA jack 3 GHz

### Description

This adapter by Delock is suitable for connecting components of radio frequency technology.



### Specification

- Connectors:
  - 1 x SMA jack >
  - 1 x RP-SMA jack
- Housing: brass gold plated
- Thread type: 1/4" - 36 UNS - 2A
- Frequency range: 3 GHz
- Impedance: 50 Ohm
- Operating temperature: -10 °C ~ 50 °C
- Dimensions (LxD): ca. 17.33 x 7.00 mm

### System requirements

- Device with one free SMA or RP-SMA port

### Package content

- Adapter

### Item no. 89992

EAN: 4043619899920

Country of origin: Taiwan, Republic of China

Package: Poly bag

**Interface**

|              |                                    |
|--------------|------------------------------------|
| Connector 1: | <b>standard</b><br>1 x RP-SMA jack |
| Connector 2: | <b>standard</b><br>1 x SMA jack    |

**Technical characteristics**

|                        |                                   |
|------------------------|-----------------------------------|
| Frequency range:       | <b>standard</b><br>3 GHz          |
| Operating temperature: | <b>standard</b><br>-10 °C ~ 50 °C |

**Physical characteristics**

|                   |                                       |
|-------------------|---------------------------------------|
| Housing material: | <b>standard</b><br>Brass gold plated  |
| Length:           | <b>standard</b><br>17.33 mm           |
| Thread type:      | <b>standard</b><br>1/4" - 36 UNS - 2A |