

Delock PCI Express 4.0 x16 Card to 4 x internal U.2 NVMe SFF-8639 - Bifurcation (LxW: 288 x 122 mm)

Description

This PCI Express card by Delock expands the PC by **four U.2 interfaces**. It supports the connection of up to four U.2 SSDs in 2.5" format.

PCIe Bifurcation

The card requires the **PCIe bifurcation** of the motherboard to split the PCIe signal in order to use multiple ports.

Note

Without PCIe bifurcation only the first SFF-8639 port of the card can be used.



Item no. 90169

EAN: 4043619901692

Country of origin: China

Package: Box

Specification

- Connectors:
internal:
4 x U.2 SFF-8639 female
1 x PCI Express x16, V4.0
1 x SATA 15 pin plug (optional for power supply)
- Supports NVM Express (NVMe)
- 4 x LED indicator for power and activity
- Bootable, ex UEFI version 2.3.1
- Supports S.M.A.R.T.
- Supports TRIM
- 16 x mounting holes

System requirements


- Linux Kernel 6.2 or above
- Windows 10/10-64/11
- Windows Server 2022

- PC with one free PCI Express x16 / x32 slot
- Motherboard and BIOS with PCIe bifurcation support

Package content

- PCI Express card
- 16 x screw
- User manual

Images



General

Function:	Bootable, ex UEFI 2.3.1 TRIM S.M.A.R.T.
Supported operating system:	Windows 10 32-Bit Windows 10 64-Bit Windows 11 Windows Server 2022 Linux Kernel 6.2 or above
LED indicator:	4 x

Interface

Internal:	1 x SATA 15 pin plug 4 x U.2 SFF-8639 Buchse 1 x PCI Express x16, V4.0
-----------	--