

InLine® HDMI Videowall controller 1 to 9, Full-HD



* Preise inkl. gesetzlicher MwSt. zzgl. Versandkosten

Marke: INL

Bestell-Nr.: 57839I



ANWENDUNGSBEISPIEL APPLICATION EXAMPLE



This stand-alone video wall controller has been designed to use high-quality multiple displays and can duplicate or enlarge a video source and distribute it to up to nine monitors. With the InLine® HDMI Video Wall Distributor you can combine 9 monitors with a max. screen resolution of 1920x1200 to a large video wall (3x3 monitors). For the input signal you have an HDMI or VGA interface available. The InLine® HDMI Video Wall Distributor is easily controlled via an IR remote control. The extended frame compensation can help to optimally adapt the picture to the video wall. The InLine® HDMI Video Wall Distributor is the ideal solution for all professional video applications such as digital signage, advertising, A/V splitting or broadcasting.

- Create a 3x3, 2x4, 4x2 video wall from any Hi-Def source, using 8-9 HDTV displays
- Split and scale a single Hi-Def source to nine displays
- Input and Output resolutions up to 1080p Full HD and 1920x1200 (WUXGA) with HDCP compliant
- Easy to use on-screen display user interface
- Advanced Bezel Compensation feature provides compatibility with virtually any screen frame width, and allows for accurate display of the image
- IR remote control
- USB port for upgrade (reserved for future product enhancements)
- Locking power supply connector
- Wall-mountable enclosure, mount ears included
- Dimension (LxWxH): 235x134x26mm
- Weight: 870g
- Video Out: HDMI Port x9 (Lockable)
- Video In: HDMI Port x1 (Lockable), VGA x1

- Audio In: 3.5mm Earphone Jack x1
- USB: Mini-USB x1
- IR: 1 x Receiver, 1 x IR Extender (3.5mm Earphone Jack)
- LED Indicator: Red x 1 (Power), Green x 1 (Video)
- Power Adapter: 5V4A (with lock)
- Housing: Metal
- Operation Temperature: 0 ~ 40°C
- Storage Temperature: -20 ~ 60°C
- Humidity: 0~90% RH, Non-condensing