

Simplex Fiber Optic Patch Cable LC-SC OS2



Description

Fiber jumper are well defined components in international standard of structured cabling ISO/IEC11801. Due to many different network protocols created in the last 25 years , also a wide range of connectors had been developed. Some of them are still important today: LC, SC, E2000®, MPO/MTP.

Fiber jumper(patchcord) are defined as shortest connection between passive interface and active deviceport, regarding structured cabling standard. Rating of performance, known as category, as well as performance of total transmission channel, known as link class, Similar descriptions for patchcords: Connection cable, drop cable, adapter cable, interconnecting cord, Jumper

General data

Fibre type	Singlemode
Category	OS2
Number of fibres	1
Anti-kink sleeve	put-on
Type of connector connection 1	LC
Connector colour 1	blue
Type of connector connection 2	SC
Connector colour 2	blue

Cable construction

Cable type	Simplex
Cable Construction	Simplex
Cable Ø	2.0 mm

Cable sheath

Colour outer sheath	yellow
Jacket Material	LSZH

This datasheet was created automatically on 10-12-2019 . Technical changes reserved.



Simplex Fiber Optic Patch Cable LC-SC OS2

Cable sheath

Flame retardant	According to EN 50265-2-1
-----------------	---------------------------

Environmental conditions

Operating Temperature	-20 – 75 °C
Storage Temperature	-20 – 85 °C

Transmission characteristics

Quality class singlemode	B/2 nach IEC 61753-1
--------------------------	----------------------

Standards, approvals, certifications

Cable Conform to Standard	IEC 60793-2
---------------------------	-------------

Available variants

Article no.	Title	Length
O0947.0,5	Simplex Fiber Optic Patch Cable LC-SC OS2 0,5m 2,0mm Yellow 9/125µm	0.5 m
O0947.1	Simplex Fiber Optic Patch Cable LC-SC OS2 1m 2,0mm Yellow 9/125µm	1.0 m
O0947.10	Simplex Fiber Optic Patch Cable LC-SC OS2 10m 2,0mm Yellow 9/125µm	10.0 m
O0947.15	Simplex Fiber Optic Patch Cable LC-SC OS2 15m 2,0mm Yellow 9/125µm	15.0 m
O0947.2	Simplex Fiber Optic Patch Cable LC-SC OS2 2m 2,0mm Yellow 9/125µm	2.0 m
O0947.20	Simplex Fiber Optic Patch Cable LC-SC OS2 20m 2,0mm Yellow 9/125µm	20.0 m
O0947.3	Simplex Fiber Optic Patch Cable LC-SC OS2 3m 2,0mm Yellow 9/125µm	3.0 m
O0947.5	Simplex Fiber Optic Patch Cable LC-SC OS2 5m 2,0mm Yellow 9/125µm	5.0 m
O0947.7,5	Simplex Fiber Optic Patch Cable LC-SC OS2 7,5m 2,0mm Yellow 9/125µm	7.5 m

Technical drawings

OM-Klassifikation ISO/IEC 11801		OM1	OM2	OM3	OM4	OM5
Min. modale Bandbreite mit vollständiger Anregung aller Kernmoden [MHz*km]	850 nm	200	500	1500	3500	4700
	1300 nm	500	500	500	500	2470
Min. modale Bandbreite (effektive) Laser-Bandbreite [MHz*km]	850 nm	n/s	n/s	2000	4700	n/s
	1300 nm	1.5	1.5	1.5	1.5	1,5
Dämpfung [dB/km]	850 nm	3.5	3.5	3.5	3.5	3,5
	1300 nm					

accessory

39962.2	Reel Cleaner(new Version)
39926.1	Miller® Fiber Cleaning Tapes