

DATASHEET

Splicebox partially assembled LC OM3 extendable 6 Adapter



General data

Partly assembled splice box with adapters
per 12 adapters 1 splice cassette with 1 splice holder
suitable up to 4 splice cassettes
metal housing sliding unit
front panel screwed
plastic adapters
cable entries at the rear

Allgemeine Daten

With housing	True
Fibre class	OM3
Mounting method	482.6 mm (19 inch) mounting
Number of height units	1 U
Sliding	sliding version
With front plate	True
With pigtails	False

General data

Height	44.5 mm
Adapters	LC

Kabelaufbau

Fibre type	Multi mode 50/125
------------	-------------------

Abmessungen

Width	483.0 mm
-------	----------

This datasheet was created automatically on 30-01-2025 . Technical changes reserved.

DATASHEET

Splicebox partially assembled LC OM3 extendable 6 Adapter

Dimensions

Depth	244.0 mm
-------	----------

Available variants

ArtNr.	Bezeichnung	Colour	Suitable for number of couplings/adapters	Type of connector external	With number of couplings/adapters	RAL-Nummer	Steckverbindertyp innen	Kupplungsfarbe
B61901.4OM3	Splicebox partially assembled LC OM3 extendable 4 Adapter	grey	12	LC-Duplex	4	7035	LC-Duplex	aqua
B61901.6OM3	Splicebox partially assembled LC OM3 extendable 6 Adapter	grey	12	LC-Duplex	6	7035	LC-Duplex	aqua
B61901.12OM3	Splicebox partially assembled LC OM3 extendable 12 Adapter	grey	12	LC-Duplex	12	7035	LC-Duplex	aqua
B61901.24OM3	Splicebox partially assembled LC OM3 extendable 24 Adapter	grey	24	LC-Duplex	24	7035	LC-Duplex	aqua
B61901TS.6OM3	Splicebox bk partially assembled LC OM3 extendable 6 Adapter	black	12	LC-Duplex	6	9005	LC-Duplex	aqua
B61901TS.12OM3	Splicebox bk partially assembled LC OM3 extendable 12 Adapter	black	12	LC-Duplex	12	9005	LC-Duplex	aqua
B61901TS.24OM3	Splicebox bk partially assembled LC OM3 extendable 24 Adapter	black	24	LC-Duplex	24	9005	LC-Duplex	aqua

This datasheet was created automatically on 30-01-2025 . Technical changes reserved.

