

Partially Assembled Splice Boxes LC-Duplex plastic adapter, sliding version, OS2



Description

Partly assembled splice box with adapters
per 12 adapters 1 splice cassette with 1 splice holder
suitable up to 4 splice cassettes
metal housing sliding unit
front panel screwed
plastic adapters
cable entries at the rear

General data

Mounting method	482.6 mm (19 inch)-installation
With housing	True
With front plate	True
With pigtails	False
Number of height units	1
Type of connector external	LC-Duplex
Type of connector interior	LC-Duplex
Sliding	sliding version
Fibre type	Singlemode
Fibre class	OS2 gemäß ITU-T G.652.D

Dimensions

Height	44.5 mm
Width	483.0 mm
Depth	244.0 mm

Available variants

Article no.	Title	With number of couplings/adapters	Adapter colour	Suitable for number of couplings/adapters	Colour RAL-number
-------------	-------	-----------------------------------	----------------	---	-------------------

This datasheet was created automatically on 30-07-2021 . Technical changes reserved.

Partially Assembled Splice Boxes LC-Duplex plastic adapter, sliding version, OS2

B61921.6	Splicebox 6-LC-(D) Adapter	6	blue	12	grey	7035
B61921.12	Splicebox 12-LC-(D) Adapter	12	blue	12	grey	7035
B61921.24	Splicebox 24-LC-(D) Adapter	24	blue	24	grey	7035
B61921TS.6	Splicebox 6-LC-(D) Adapter	6	blue	6	Black	9005
B61921TS.12	Splicebox 12-LC-(D) Adapter	12	blue	12	Black	9005
B61921TS.24	Splicebox 24-LC-(D) Adapter	24	blue	24	black	9005

This datasheet was created automatically on 30-07-2021 . Technical changes reserved.