

DATASHEET

Warm Device Extension C14 180° - C15 180°, Black, 2 m,
3 x 1.00 mm²



General data

Plug IEC60320/C14 to jack IEC60320/C15
10 A / 250 V VDE tested
Cable H50RN-F 3G(rubber cable)
Colour black

Allgemeine Daten

Number of cores	3
Colour outer sheath	black
Spiralized cable	False
With cord switch	False
Material outer sheath	rubber
Halogen free	False

Mechanische Eigenschaften

Connection 1	Cold device plug (IEC 60320)
Connection 2	Hot device plug, female

Kabelmantel

Oil resistant (according to EN 60811-404)	False
Temperature resistance	-35 - 70 °C

Elektrische Eigenschaften

This datasheet was created automatically on 11-12-2023 . Technical changes reserved.

DATASHEET

Warm Device Extension C14 180° - C15 180°, Black, 2 m, 3 x 1.00 mm²

Protective conductor	True
Nominal voltage	250 V

Normen, Zulassungen, Zertifizierungen

Oil resistant (acc. EN 60811-2-1)	False
-----------------------------------	-------

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Degree of protection	Length	Nominal current	Nominal voltage	With protective conductor	Leiternennquerschnitt	Außendurchmesser ca.
EK585.0,5V2	Warm Device Extension C14 180° - C15 180°, Black, 0.5 m, 3 x 1.00 mm ²	black	IP20	0.5 m	10 A	- 250 V	True	1,00 mm ²	7,3 mm
EK585.1V2	Warm Device Extension C14 180° - C15 180°, Black, 1 m, 3 x 1.00 mm ²	black	IP20	1.0 m	10 A	- 250 V	True	1,00 mm ²	7,3 mm
EK585.2V2	Warm Device Extension C14 180° - C15 180°, Black, 2 m, 3 x 1.00 mm ²	black	IP20	2.0 m	10 A	- 250 V	True	1,00 mm ²	7,3 mm
EK585.3V2	Warm Device Extension C14 180° - C15 180°, Black, 3 m, 3 x 1.00 mm ²	black	IP20	3.0 m	10 A	- 250 V	True	1,00 mm ²	7,3 mm

This datasheet was created automatically on 11-12-2023 . Technical changes reserved.

