



LogiLink®


DIN-Rail Mechanical Time Switch

Art. No.: ET0009

24 hours programming Time switch controls any electrical installation, such as neon lights, water heater, street lamps, garden watering and other civilian or industrial electricity needs time control of the occasion, according to the required time for automatic control.

Specification:

Input Voltage	220-240V AC 50/60Hz
Switch Capacity	16(4)A 250V AC
Power Consumption	0.5W
Power Reverse (QRD/QRS)	100 hours
Minimum Function Time	Daily: 15 minutes; Weekly: 2 hours
Type of Dial	Daily: 96 pins
Manual Operating Switch	2 Positions: ON-Automatic
Operating Accuracy	±3 sec/day at 22°C
Operating Temperature	-10°C to 50°C
Protection	IP20
Dimension	1 Din



Package Contents:

- » 1 x Din-Rail Mechanical Timer Switch
- » 1 x User Manual

Package Information:

- » Packing Dimension: 103 x 69 x 19mm
- » Packing Weight: 0.08kg
- » Carton Dimension: 360 x 210 x 115mm
- » Carton Q'ty: 50pcs
- » Carton Weight: 4.2kg



*If the time switch is to be used in combination with other devices; it is necessary to verify that no parasitic disturbances will be caused by the group.



RoHS
compliant



* The specifications and pictures are subject to change without notice.
*All trade names referenced are the registered namework of their respective owners.



ET0009



Made in China