



Model: PD-2036

Art.: 88882227

Small 36W PD-Charger, supporting PD-Charging with 5V, 9V, 12V, 15V and 20V.

Concurrent operation of two USB Type C devices possible.

Input	Voltage	AC 100 - 240 V ~
	Current	max 0.35A
	Frequency	50/60Hz
Output	Power	max. 36W
	Current	max. 3,0A
	Voltage	5V= (max. 3,0A)
		9V= (max. 3,0A)
		12V= (max. 3,0A)
		15V= (max. 2,4A)
		20V= (max.1,8A)
		5V= (max. 2x 3,0A) bei gleichzeitiger Nutzung beider USB Ausgänge 9V= (max. 2x 2,0A) bei gleichzeitiger Nutzung beider USB Ausgänge 12V= (max. 2x 1,5A) bei gleichzeitiger Nutzung beider USB Ausgänge
	Connector	2x USB Type C
Safety	Short Circuit Protection	+
	Over Power Protection	+
Economic data	Efficiency	85,00%
	Standby	< 0,1W
Environmental	Temperature	0°C - 40°C (Operating) -20°C - 85°C (Storage)
	Humidity	5% - 90% (Operating, non condensing) 0% - 95% (Storage, non condensing)
Scope of delivery		PD Charger, Manual
Warranty		12 Months
Logistic data	Dimension	69 x 50 x 50 mm
	Net weight	80 g
	Gross weight	95 g
	Article number	88882227
	GTIN	4260455648240
	Packing unit	1 pcs