



NLS-1250-70

1D CCD Handheld Scanner



Brief Overview:

Newland is proud to present the first model of its ecofriendly future forward product line. The brand new Newland HR1250-70 handheld barcode scanner incorporates the latest Newland 1D decoding chip technology for excellent 1D barcode scanning performance at exceptionally low power consumption. The HR1250-70 can perform up to 300 scans per second, which translates into very fast and accurate barcode capturing. In addition, its compact size, ergonomic and solid state design makes a smart solution for extensive use in varied environments. The HR1250-70 is a practical no frills, user friendly quality entry level scanner at an extremely competitive price.

Features:



Ergonomic Design

The relatively small design of the HR1250-70 (163.0 x 68.4 x 58.5 mm L x W x H) combined with the low weight (130g with USB) and solid state design makes for a reliable and easy to handle scanner.



Superior decoding performance

Delivers speedy and accurate(built-in laser aimer) scanning performance and supports most 1D barcode symbologies



Ecofriendly

Newland's HR1250-70 operates on $55\text{mA} \pm 5\text{mA}$ current only. This means increased energy savings and an ecofriendly business solution.

Specifications

Performance

Image Sensor / Illumination		CCD / Red LED (610-640 nm)
Scan Rate		Up to 300 scans per second
Symbologies	1D	EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Codabar, Code 128, Code 93, ITF-6, ITF-14, Interleaved 2 of 5, Industrial 2 of 5, Standard 2 of 5, Matrix 2 of 5, GS1 Databar, Code 39, Code 11, MSI-Plessey, Plessey.
Reading Precision		≥ 4mil
Depth of field		UPCA - 13 mil - 35mm- 600mm EAN-13- 13mil- 40mm- 585mm Code 39- 5mil- 45mm- 155mm
Scan Angle**		Roll: ±30°; Pitch: ±60°; Skew: ±60°
Minimum symbol contrast		30%

Mechanical/Electrical

Dimensions		163.0 x 68.4 x 58.5 mm (L x W x H)
Weight		130g(USB data cable included)
Current (DC 5V)	Maximum	<120 mA
	Operating	55 mA ± 5mA
	Idle	21 mA ± 5mA
Interface		USB

Environmental

Operating Temperature	-20°C to +60°C
Storage Temperature	-40°C to +85°C
Humidity	5% to 95% (non-condensing)
Static Discharge	±8kV (contact discharge); ±10kV (air discharge)

Certifications

FCC Part15 Class B, CE EMC Class B

**Test conditions:

Code 39, 3 Bytes; Resolution=10mil; W:N=2.5:1; PCS=0.8; Barcode Height=40mm; Scan Distance=210mm, T=23°C, Illumination= 200 LUX

Contact Us:

Newland EMEA
+31(0) 345 87 00 33
info@newland-id.com

Newland Nordic
+46 (0) 708 847 767
Goeran@newland-id.com

Newland UK Branch
+44 (0) 1442 212 020
info@newland-id.co.uk

Newland France Branch
+33 (0) 160 707 974
info@newland-id.fr

Newland D-A-CH
+49 (0) 294 298 76758
info@newland-id.de

Newland Italy Branch
+39 (0) 335 773 0521
Cristiano@newland-id.com

www.newland-id.com

Specifications are subject to change without notice.

Datasheet v.1.0.0

