

正面



Figure 10 consists of two plots. The top plot is a line graph of Frequency Response (dB rel. 1V/Pa, 1kHz) versus frequency (50 to 20K Hz). The y-axis ranges from -30 to +20 dB. The response is relatively flat, staying between -5 dB and +5 dB. The bottom plot is a polar plot of Polar Response (dB rel. 1V/Pa) at 1kHz. The y-axis ranges from -25.0 to +5.0 dB. The plot shows a circular response with a slight dip at 180 degrees, indicating a slight rearward response.

Shock Mount

Microphone stand

Pop filter

Table Clamp

USB Cable

Windscreens cap

-

Skype Contacts Conversation Call View **Tools** Help

Skype™ - Options

General

Audio settings: Set up sound on your computer

General settings

Audio settings

Sounds

Video settings

Skype Translator

Microphone

USB Condenser Microphone

Volume

Speakers

Speakers (Realtek High Definition Audio)

Automatically adjust microphone settings

Automatically adjust speaker settings

Sound

Sound Effects Output **Input**

Select a device for sound input:

Name	Type
Internal Microphone	Built-In
USB Condenser Microphone	USB

Settings for the selected device:

The selected device has no input controls

Input level: ○ ○ ○ ○ ○ ○ ○ ○ ○ ○

背面

