



8-Line Professional Carrier-Grade IP Phone

GRP2624

Part of the GRP series of Carrier-Grade IP Phones, the GRP2624 is a professional 8-line model designed with zero-touch provisioning for mass deployment and easy management. It features a sleek design and a suite of next-generation features including: 5-way voice conferencing to maximize productivity, integrated Wi-Fi, Bluetooth support, full HD audio on both the speaker and handset to provide the utmost clarity, EHS support for Plantronics headsets and USB to support Grandstream's GUV Series headsets. The GRP2624 is compatible with the GBX20 Extension Module that adds functionality, versatility and flexibility with up to 40 contacts per module and support for up to 160 contacts by connecting 4 extension modules. The GRP series includes carrier-grade security features to provide enterprise-level security, including secure boot, dual firmware images and encrypted data storage. For cloud provisioning and centralized management, the GRP2624 is supported by Grandstream's Device Management System (GDMS), which provides a centralized interface to configure, provision, manage and monitor deployments of Grandstream endpoints. The GRP2624 is the perfect choice for busy professionals and receptionists who need to manage high call volumes, with advanced functionality. Designed for easy deployment by enterprises, service providers and other high-volume markets, the GRP2624 offers an easy-to-use and easy-to-deploy voice endpoint.



8 lines, 4 SIP accounts



Supported by GDMS which provides a centralized interface to configure, provision, manage and monitor Grandstream devices



Integrated Bluetooth to connect headsets, sync contacts, calendars and more



Full-duplex speakerphone with HD audio to maximize audio quality and clarity



Equipped with noise shield technology to minimize background noise



Dual switched auto-sensing 10/100/1000 Mbps Gigabit Ethernet ports with integrated PoE



Supports 5-way audio conferencing for easy conference calls



Enterprise-level protection including secure boot, dual firmware images, and encrypted data storage



Swappable faceplate to allow for easy logo customization



Integrated dual-band Wi-Fi 802.11 a/b/g/n/ac (2.4Ghz & 5Ghz)

Protocols/Standards	SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP, ICMP, DNS(A record, SRV, NAPTR), DHCP, PPPoE, TELNET, TFTP, NTP, STUN, SIMPLE, LLDP, LDAP, TR-069, 802.1x, TLS, SRTP, IPV6
Network Interfaces	Dual switched auto-sensing 10/100/1000 Mbps Gigabit Ethernet ports with integrated PoE
Graphic Display	2.8 inch (320x240) TFT color LCD
Wi-Fi	Yes, integrated dual-band Wi-Fi 802.11 a/b/g/n/ac (2.4Ghz & 5Ghz)
Bluetooth	Yes, integrated
Feature Keys	8 line keys with up to 4 SIP accounts, 4 XML programmable context sensitive softkeys, 5 navigation/menu keys, 9 dedicated function keys for: MESSAGE(with LED indicator), TRANSFER, HOLD, HEADSET, MUTE, SEND/REDIAL, SPEAKERPHONE, VOL+, VOL-
Auxiliary Port	RJ9 headset jack allowing EHS with Plantronics headsets, USB to support Grandstream's GUV Series headsets and other USB headsets
Voice Codecs and Capabilities	Support for G.729A/B, G.711μ/a-law, G.726, G.722 (wide-band), G.723, iLBC, OPUS, in-band and out-of-band DTMF (in audio, RFC2833, SIP INFO)
Telephony Features	Hold, transfer, forward, 5-way conference, call park, call pickup, shared-call-appearance(SCA)/bridged-line-appearance(BLA), downloadable phonebook(XML, LDAP, up to 2000 items), call waiting, call log(up to 2000 records), XML customization of screen, off-hook auto dial, auto answer, click-to-dial, flexible dial plan, hot-desking, personalized music ringtones and music on hold, server redundancy and fail-over
HD Audio	Yes, HD handset and speakerphone with support for wideband audio, and dual microphone.
Extension Module	Yes, GBX20
Base Stand	Yes, 2 angle positions available, Wall Mountable (Wall Mount *sold separately)
QoS	Layer 2 QoS (802.1Q, 802.1P) and Layer 3 (ToS, DiffServ, MPLS) QoS
Security	User and administrator level passwords, MD5 and MD5-sess based authentication, 256-bit AES encrypted configuration file, SRTP, TLS, 802.1x media access control, secure boot.
Multi-language	English, German, Italian, French, Spanish, Portuguese, Russian, Croatian, Chinese, Korean, Japanese and more
Upgrade/Provisioning	Firmware upgrade via FTP/TFTP / HTTP / HTTPS, mass provisioning using GDMS/TR-069 or AES encrypted XML configuration file.
Power & Green Energy Efficiency	Universal power adapter included: Input: 100-240V ; Output: +12V, 1A ; Integrated Power-over-Ethernet (802.3af) Max power consumption 9.5W (power adapter) or 10.8W (PoE)
Temperature and Humidity	Operation: 0°C to 40°C Storage: -10°C to 60°C Humidity: 10% to 90% Non-condensing
Package Content	GRP2624 phone, handset with cord, phone stand, 12V power adapter, network cable, Quick Installation Guide, GPL license
Physical	Dimension: 220mmx 210mmx 82mm Unit Weight: 880g ; Package Weight:1260g