


U/UTP 4Pairs cable-category5E-PVC Sheath

P/N: HK-1191-C5E-003-01

Content of the Data Sheet

Content of the Data Sheet																																																																																																																									
	HIKVISION E484059-Z CMX (UL) 4PR 24AWG 75 ℃ U/UTP CAT5E VERIFIED TO ANSI/TIA-568-C.2 PVC ****m mm/dd/yyyy																																																																																																																								
Customer Reference					White-Blue /Blue White-Orange/Orange Sheath Rip-cord White- Brown /Brown White- Green /Green 																																																																																																																				
Category	U/UTP CAT5E-4P- PVC-CMX																																																																																																																								
Test Standard	ISO/IEC11801、TIA-568-C.2 YD/T1019																																																																																																																								
Conductor	Material	Solid-Bare Copper																																																																																																																							
	Copper content	99.97%																																																																																																																							
	Nom.O.D.(mm)	0.450	up	+0.005																																																																																																																					
			down	-0.005																																																																																																																					
Insulation	Material	HDPE																																																																																																																							
	Diameter	0.82±0.03mm																																																																																																																							
Sheath	Thickness	0.50±0.05 mm			Technical Performance(100m): <table><thead><tr><th>Frequency (MHz)</th><th>RL ≥dB</th><th>ATT ≤dB</th><th>NEXT ≥dB</th><th>Phase ≤ns</th><th>DELAY</th></tr></thead><tbody><tr><td>1</td><td>19.0</td><td>3.0</td><td>60.0</td><td>521</td><td></td></tr><tr><td>4.0</td><td>19.0</td><td>3.9</td><td>54.8</td><td>504</td><td></td></tr><tr><td>8.0</td><td>19.0</td><td>5.5</td><td>50.0</td><td>500</td><td></td></tr><tr><td>10.0</td><td>19.0</td><td>6.2</td><td>48.5</td><td>498</td><td></td></tr><tr><td>16.0</td><td>19.0</td><td>7.9</td><td>45.2</td><td>496</td><td></td></tr><tr><td>20.0</td><td>19.0</td><td>8.9</td><td>43.7</td><td>495</td><td></td></tr><tr><td>25.0</td><td>18.0</td><td>10.0</td><td>42.1</td><td>495</td><td></td></tr><tr><td>31.25</td><td>17.1</td><td>11.2</td><td>40.5</td><td>494</td><td></td></tr><tr><td>62.5</td><td>14.1</td><td>16.2</td><td>35.7</td><td>492</td><td></td></tr><tr><td>100</td><td>12.0</td><td>21.0</td><td>32.3</td><td>491</td><td></td></tr></tbody></table> <table><thead><tr><th>Frequency (MHz)</th><th>PSNEXT ≥dB</th><th>ELFEXT ≥dB</th><th>PSELFEXT ≥dB</th></tr></thead><tbody><tr><td>1</td><td>57.0</td><td>58.6</td><td>55.6</td></tr><tr><td>4</td><td>51.8</td><td>46.6</td><td>43.6</td></tr><tr><td>8</td><td>47.0</td><td>40.6</td><td>37.5</td></tr><tr><td>10</td><td>45.5</td><td>38.6</td><td>35.6</td></tr><tr><td>16</td><td>42.2</td><td>34.5</td><td>31.5</td></tr><tr><td>20</td><td>40.7</td><td>32.6</td><td>29.6</td></tr><tr><td>25</td><td>39.1</td><td>30.7</td><td>27.7</td></tr><tr><td>31.25</td><td>37.5</td><td>28.7</td><td>25.7</td></tr><tr><td>62.5</td><td>32.7</td><td>22.7</td><td>19.7</td></tr><tr><td>100</td><td>29.3</td><td>18.6</td><td>15.6</td></tr></tbody></table>							Frequency (MHz)	RL ≥dB	ATT ≤dB	NEXT ≥dB	Phase ≤ns	DELAY	1	19.0	3.0	60.0	521		4.0	19.0	3.9	54.8	504		8.0	19.0	5.5	50.0	500		10.0	19.0	6.2	48.5	498		16.0	19.0	7.9	45.2	496		20.0	19.0	8.9	43.7	495		25.0	18.0	10.0	42.1	495		31.25	17.1	11.2	40.5	494		62.5	14.1	16.2	35.7	492		100	12.0	21.0	32.3	491		Frequency (MHz)	PSNEXT ≥dB	ELFEXT ≥dB	PSELFEXT ≥dB	1	57.0	58.6	55.6	4	51.8	46.6	43.6	8	47.0	40.6	37.5	10	45.5	38.6	35.6	16	42.2	34.5	31.5	20	40.7	32.6	29.6	25	39.1	30.7	27.7	31.25	37.5	28.7	25.7	62.5	32.7	22.7	19.7	100	29.3	18.6	15.6
	Frequency (MHz)	RL ≥dB	ATT ≤dB	NEXT ≥dB								Phase ≤ns	DELAY																																																																																																												
	1	19.0	3.0	60.0								521																																																																																																													
	4.0	19.0	3.9	54.8								504																																																																																																													
	8.0	19.0	5.5	50.0								500																																																																																																													
10.0	19.0	6.2	48.5	498																																																																																																																					
16.0	19.0	7.9	45.2	496																																																																																																																					
20.0	19.0	8.9	43.7	495																																																																																																																					
25.0	18.0	10.0	42.1	495																																																																																																																					
31.25	17.1	11.2	40.5	494																																																																																																																					
62.5	14.1	16.2	35.7	492																																																																																																																					
100	12.0	21.0	32.3	491																																																																																																																					
Frequency (MHz)	PSNEXT ≥dB	ELFEXT ≥dB	PSELFEXT ≥dB																																																																																																																						
1	57.0	58.6	55.6																																																																																																																						
4	51.8	46.6	43.6																																																																																																																						
8	47.0	40.6	37.5																																																																																																																						
10	45.5	38.6	35.6																																																																																																																						
16	42.2	34.5	31.5																																																																																																																						
20	40.7	32.6	29.6																																																																																																																						
25	39.1	30.7	27.7																																																																																																																						
31.25	37.5	28.7	25.7																																																																																																																						
62.5	32.7	22.7	19.7																																																																																																																						
100	29.3	18.6	15.6																																																																																																																						
External O.D.	4.7±0.4 mm																																																																																																																								
Surface	Clean,Frap,Satiation																																																																																																																								
Material	PVC(complies RoHS),CM																																																																																																																								
Color	Grey ZLC1003																																																																																																																								
Surface Printing	Letter height	3.0±0.3mm																																																																																																																							
	Color	Black																																																																																																																							
	Print error & Space	≤±0.5%, 1m																																																																																																																							
Core Color	1 White- Blue /Blue	2 White-Orange /Orange																																																																																																																							
	3 White- Green /Green	4 White- Brown /Brown																																																																																																																							
Packing	Wooden Tray & Carton																																																																																																																								
Carton dimension	Per request																																																																																																																								
Packing length	305±1.5m/80±0.5m																																																																																																																								
Rip-cord	Yes	Drain wire	No																																																																																																																						
Sheath Physical Properties	Before Aging	Tensile Strength (Mpa) ≥13.5																																																																																																																							
		Elongation(%) ≥150																																																																																																																							
	Aging Period(℃×hrs)	100℃×24h×10d																																																																																																																							
	After Aging	Tensile Strength(Mpa) ≥12.5																																																																																																																							
		Elongation(%) ≥125																																																																																																																							
	Cold bend(-20±2℃×4h) 8×Cable O.D., No visible cracks																																																																																																																								
Electrical Characteristics (20℃)	1.0-100.0MHz	Impedance(Ω)		100±15																																																																																																																					
	1.0-100.0MHz	Delay Shew (ns/100m)		≤45																																																																																																																					
	DC ResistanceΩ/100m) max		14.8																																																																																																																						
	DC Conductor Resistance Unbalance(%) max		5.0																																																																																																																						
Ambient temperature: -20℃ - 70℃																																																																																																																									