

Picture



Model

E Series E560P

Video & Audio

Image Sensor	1/2.8" CMOS Sensor
Video Resolution	3840X2160(8Megapixels)@25FPS
Lens	2.8mm ~ 8mm, Zoom Module
Video Format	H.265
Field of View	Horizontal: 94° ~ 50° Vertical: 53° ~ 30°
Day & Night	IR-cut filter with auto-switching
Infrared Night Vision	Up to 12 Meters (40ft)(LED: 12pcs/14mil/850nm)
Color Night Vision	4pcs/2.7W/6500K/180Lumens
Audio	Two-way Audio

Power

POE	IEEE 802.3af, 48V Active
DC Power	DC 12.0V=1A, <12W

Interface

Power	DC power port
System	Reset Button
Ethernet	One 10M/100Mbps RJ45
Storage	MicroSD card slot (Max. 256GB)
Audio	Built-in Microphone and Speaker

Pan&Tilt

Pan &Tilt Range	Pan: 355°, Tilt: 0°~50°
Auto Tracking	Support

Software Features

Frame Rate	Main Stream: 2fps - 25fps(default: 25fps) Sub Stream: 4fps - 15fps(default: 10fps)
Code Rate	Main Stream: 4096Kbps -8192Kbps(default: 6144Kbps) Sub Stream: 64Kbps - 512Kbps(default: 256Kbps)
Browser Supported	Edge, Chrome, Firefox, Safari
OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
Smart Alarm	Motion detection/Human Detection/Vehicle Detection/Pet Detection
Record Mode	Motion Record/Schedule Record (Default: Motion Record)
Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, HTTP, IPv4, UPnP, RTSP, RTMP, ONVIF, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P
Maximal User Access	Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams) 20 Users (1 admin account & 19 user accounts);
Work with	Google Assistant, Reolink NVR

Working Environment

Temperature	Operating Temperature: -10°C~+50°C (14°F~122°F)
Humidity	Operating Humidity: 10% ~ 90%
Waterproof	IP65

Size & Weight

Dimension	Ø90 x 120mm
Weight	446g

Warranty

Limited Warranty	2-year limited warranty. For support, visit <a href="https://support.reolink.com/hc/en-us/">https://support.reolink.com/hc/en-us/</a>
------------------	---