






8-Port Unmanaged 2.5G Switch

TEG-S380 (v1.0R)

- 8 x 2.5GBASE-T ports
- IEEE 802.3bz (2.5G) compliant
- Backwards compatible with 10/100/1000Mbps devices
- 40Gbps switching capacity
- Fanless design eliminates noise
- Wall mountable for installation flexibility
- Lifetime Warranty

Expand your network's bandwidth and reduce digital bottlenecks with TRENDnet's Unmanaged 2.5G Switches. These 2.5G network switches come equipped with 2.5GBASE-T RJ-45 ports that provide higher gigabit speeds capable of up to 2.5Gbps over your existing Cat5e or better cabling. Each high-speed 2.5G switch features a durable metal enclosure and can be mounted to the wall for setup flexibility. The fanless design lowers energy consumption and eliminates distracting operating noise. TRENDnet's reliable 2.5G switches are cost-effective solutions to increase your network's throughput.



2.5G Ports

Equipped with 2.5GBASE-T RJ-45 ports that provide higher gigabit speeds capable of up to 2.5Gbps over existing Cat5e or better cabling.



Wall Mountable

The 2.5G switches feature metal housing with a convenient wall mountable design for greater installation flexibility.

Fanless

The fanless design of the 2.5G switches lowers energy consumption costs and eliminates operating noise.

NETWORKING SOLUTION



FEATURES



Easy Installation

No configuration needed, simply connect network devices to the 2.5G Ethernet switch



2.5G Ports

Equipped with 2.5GBASE-T RJ-45 ports that provide higher gigabit speeds capable of up to 2.5Gbps over existing Cat5e or better cabling



Fanless

Fanless design lowers energy consumption and eliminates operating noise



Housing Design

Sturdy metal housing



Wall Mountable

Features a convenient wall mountable design for greater installation flexibility



Jumbo Frame

Sends larger packets, or Jumbo Frames (up to 12KB) for increased performance



LED Indicators

LED indicators on this 2.5G switch convey port status

SPECIFICATIONS

Standards

- IEEE 802.3
- IEEE 802.3u
- IEEE 802.3x
- IEEE 802.3z
- IEEE 802.3ab
- IEEE 802.3az
- IEEE 802.3bz

Device Interface

- 8 x 2.5GBASE-T ports (100Mbps/1Gbps/2.5Gbps)
- LED indicators

Data Transfer Rate

- Ethernet: 10Mbps (half duplex), 20Mbps (full duplex)
- Fast Ethernet: 100Mbps (half duplex), 200Mbps (full duplex)
- Gigabit: 2000Mbps (full duplex)
- 2.5 Gigabit: 5Gbps (full duplex)

Performance

- Switching Capacity: 40Gbps
- RAM Buffer: 1.5MB
- MAC Address Table: 16K entries
- Forwarding Rate: 29.76Mpps (64-byte packet size)
- Jumbo Frames: 12KB

Special Features

- Wall-Mountable

Power

- Input: 100 – 240V AC, 50/60 Hz, 0.6A
- Output: 12V DC, 1.5A
- Max. Consumption: 12.4W

Fan/Acoustics

- Fanless design

MTBF

- 1,401,356 hours

Operating Temperature

- 0° – 40° C (32° – 104° F)

Operating Humidity

- Max. 90% non-condensing

Dimensions (L x W x H)

- 240 x 103 x 26mm (9.4 x 4.0 x 1.02 in.)

Weight

- 600g (1.32 lbs.)

Certifications

- FCC
- CE

Warranty

- Lifetime

Package Contents

- TEG-S380
- Quick Installation Guide
- Power adapter (12V DC, 1.5A)

TRENDnet offers a lifetime warranty for all of its metal-enclosed network switches that have been purchased in the United States/Canada on or after 1/1/2015. Cooling fan and internal power supply carry a one-year warranty.