



BE-8010S - BE-8065S

**ERGO™ VDE Insulated Slotted
Screwdrivers with 3-Component
Handle 0.4 mm-2 mm**



PRODUCT DETAILS

- Screwdriver developed according to the scientific ERGO™ process
- ERGO™ insulated VDE screwdriver for slotted head screws
- Phosphate finish tip for higher accuracy
- three-component handle for maximum user comfort, soft material with ridged surface provides superior grip and greater force transmission
- Anti-roll flat face on handle
- Integrated hanging hole
- Easy to choose the right tip with the colour-coded handle and permanent symbol on the domed end
- No colour identification in extra small handle, small sizes from 2.5 to 3.5
- High-performance alloy steel, insulation moulded directly onto blade
- For work on live equipment up to 1000 V
- Individually inspected and manufactured according to IEC 60900, tested in a water bath at 10000 V
- Standards: ISO 2380/DIN 5264



Follow the Fish!



PRODUCT ATTRIBUTES

Product							
BE-8010S	0.4 mm	2.5 mm	75 mm	17 mm	103 mm	178 mm	30 g
BE-8220S	0.5 mm	3.0 mm	100 mm	17 mm	103 mm	203 mm	33 g
BE-8230S	0.6 mm	3.5 mm	100 mm	17 mm	103 mm	203 mm	33 g
BE-8040S	0.8 mm	4.0 mm	100 mm	20 mm	122 mm	222 mm	33 g
BE-8050S	1.0 mm	5.5 mm	125 mm	27 mm	122 mm	247 mm	62 g
BE-8255S	1.2 mm	6.5 mm	150 mm	36 mm	122 mm	272 mm	105 g
BE-8065S	1.2 mm	8.0 mm	175 mm	36 mm	122 mm	297 mm	127 g
BE-8258S	1.6 mm	10 mm	200 mm	36 mm	161 mm	361 mm	270 g
BE-8259S	2.0 mm	12 mm	200 mm	36 mm	161 mm	361 mm	280 g

Follow the Fish!

