



Active holder for fixed installation

Fits for devices with original skin. With tilt swivel. With Easy-switching system. 2,7A charger via pogo pins. 12/24 Volt. With AMPS, VESA 75 holes.

Item no: 713386

EAN Number: 7320287133868

Use an active holder for your Galaxy Tab Active while driving and you will always have a freshly charged battery! The active holder is to be connected inside the dashboard. It provides a discreet and neat installation without any cables hanging over the interior. Safe and convenient! 12/24 Volt. The product is E-approved. Connect the power cable with a 2A fuse. 2,7A charger. Charging via pogo plug. Professional installation recommended.

The holder is equipped with a tilt swivel so you can easily adjust the angle for better viewing. Tilts 17° and swivels 360°. Mounting plate 42x50 mm with 4 mm AMPS-holes. Made of high grade black ABS/Acetal plastic. Made in Sweden.

Easy-switching system:

The easy-switching system enables you to upgrade the holder only, and keep the installed cables. It saves you a lot of time! When upgrading to a new device, you do not longer need to make a full installation. Same goes for maintenance in case of warranty or damage. You simply disconnect the holder from the charging cable via the Molex 6-pin quick connector, and then connect the new holder. The switch is done in a few seconds.

Choose installation placement with care, devices must not be placed in positions where they may block the view or important controls. The cradle should only be attached onto a suitable place. Installations always take place at the customer's own discretion and responsibility.

Fits the following models:

Samsung Galaxy Tab Active 3 SM-T570/SM-T575
Samsung Galaxy Tab Active 5 SM-X300/SM-X306B

Measurements:

Height 167 mm
Width 247 mm
Depth 52 mm
Volume 2145 cm³
Weight 492 g

Charging specifications:

Input voltage: DC/10-30V
Charging voltage: DC/4.75-5.4V
Output current(Typ): 2.7A
Input & output protection: Input polarity reversal/Output over voltage/Output over current/Output short protection
LED charging indicator: Power input indicator(Green), Ovp/Ocp/Output short (Red)
Operating temperature: 0°C ~ +40°C
Storage temperature: -20°C ~ +80°C
RoHS compliant: ROHS

For a complete list, see

www.brodit.com/en/product/713386