



Active holder for fixed installation

With USB Type-C. With 2 USB ports: Type-A and Type-C, QC 3.0A + 2.4A. With tilt swivel. 12/24 Volt. Adjustable holder for devices with skin with the following dimensions: Width: 70-83 mm, Thickness: 6-10 mm.

Item no: 727370

EAN Number: 7320287273700

With your mobile in a holder while driving you will always have it within easy sight and reach! And with an active holder you always have a charged battery when leaving the car. Neat, discreet and convenient! For fixed installation. The holder is to be connected inside the dashboard, providing an elegant installation without any cables hanging over the interior. The charging box has two USB ports: QC 3.0A + 2.4A. It is easy to slide the device in place in the holder so it connects to the charging, and to take it out of the holder when leaving the vehicle.

The holder is equipped with a tilt swivel so you can easily adjust the angle for better viewing. Tilts 17° and swivels 360°. Mounting plate 42x50 mm with 4 mm AMPS-holes. Made of high grade black ABS/Acetal plastic. Made in Sweden. Connect the power cable with a 2A fuse. Professional installation recommended.

The adjustable holder fits for devices with skin with the following dimensions: Width: 70-83 mm, Thickness: 6-10 mm. Adjustable holders come in various sizes. Measure your device and compare with the holder specifications in order to make sure you have chosen the correct product.

Before using the holder you need to set the holder's width so it suits your device, then your phone is held firmly in place in an upright position for maximum cellular reception. The holder has a neat and discreet design which blends well with the vehicle's interior. Attach onto ProClip Mounting Platform.

This product supports Qualcomm QC 3.0 quick charge (provided the device supports Qualcomm QC 3.0 quick charge).

Fits the following models:

Apple iPhone 15
Apple iPhone 15 Pro

For a complete list, see

www.brodit.com/en/product/727370

Measurements:

Height 90 mm
Width 73 mm
Depth 54 mm
Volume 355 cm³
Weight 216 g

Charging specifications:

- Output Connector Type: USB-A + TYPE-C PD
- Output Voltage: 5V, 9 V, 12 V (Nominal)
- Output Current:
- USB Port 1: TYPE-C PD: 3.6V ~ 6V/3A 6.2-9V/2A 9.2-12V/1.5A (Under full Load)
- USB Port 2: USB-A Port 2: 5V/3A 9V/2A 12V/1.5A (No Device attached)
- Output Voltage Ripple: 300mV pk-pk at Max Load
- Input Voltage Range: DC 12--24V DC, Input can handle 40V Load dump transient events
- Input Current: 3.0 A DC Max
- Input Current with No device attached: 0.005A
- DC-DC Conversion Efficiency: Over 86% Typical
- Rated Power:
- USB Port 1: 18 Watts Max. White port.
- USB Port 2: 18 Watts Max. Green port.