

AXIS T91H61 Wall Mount

Quick connection and room for more

Designed for fixed dome cameras, AXIS T91H61 Wall Mount accommodates and safely protects accessories inside the mount. Connect to power and data quickly and easily with the built-in RJ45 cable and connection. Designed to be impact- and weather-resistant, this mount is suitable for all environments both indoors and outdoors. It can be mounted on poles and corners with the help of optional accessories.

- > Room for connectivity devices, midspans (not included) and service loop
- > Protection against impacts, rain, dust and corrosion
- > Built-in RJ45 cable with connector



AXIS T91H61 Wall Mount

General			
Supported products	All camera pendant kits with 1.5" NPS thread mount, such as: AXIS P32-VE cameras (requires camera specific pendant kit) AXIS P33-VE cameras (requires camera specific pendant kit) AXIS Q35-VE cameras (requires camera specific pendant kit) AXIS Q36-VE cameras (requires camera specific pendant kit) AXIS P3707-PE camera (requires camera specific pendant kit) For a complete list of compatible cameras, please visit: http://www.axis.com/se/sv/products/accessory-selector		IEC/EN 60529 IP66, IEC 62262 IK10, IEC 60068-2-6 (Sinus), IEC 60068-2-27 (Shock), NEMA 250 Type 4X, UL 50E, MIL-STD 810G 509.5, RoHS
Casing	Powder coated aluminum casing Color: white NCS S 1002-B	Included accessories	Installation guide Ethernet cable with male-to-male RJ45 connectors (with gasket C M20) Foam gaskets and silicone strap (pre-mounted) Cable ties
Dimensions	185 x 214 x 404 mm (7.28 x 8.43 x 15.9 in)	Optional accessories	AXIS T8120 Midspan 15 W 1-port AXIS T81B22 DC 30 W Midspan 1-port ^a AXIS T8133 30 W Midspan ^a AXIS T8642 PoE+ over Coax Device AXIS T91A57 Pole Mount AXIS T91A64 Corner Mount AXIS ACI Conduit Adapters Network cable coupler indoor slim For more accessories, see www.axis.com
Weight	3.9 kg (8.6 lb)	Warranty	3-year warranty, see axis.com/warranty
Maximum load	30 kg (66 lb)	a. <i>Midspan not included</i>	
Cable routing	Back: cable hole Bottom: 3/4" Conduit entrance x2	Environmental responsibility: axis.com/environmental-responsibility	
Environment	Indoor Outdoor		
Approvals	Safety IEC/EN/UL 60950-1, IEC/EN/UL 60950-22 Environment		