

AXIS TQ1808-VE Surveillance Cabinet

Extended cabinet for installation of critical system equipment

AXIS TQ1808-VE is designed with the integrator in mind to ensure that the product can be installed efficiently. The cabinet itself ships empty and can be ordered stand alone, but it's also possible to buy its spare part AXIS T1807-VE Cabinet Door, to add a deeper door to AXIS T98A15-VE Surveillance Cabinet. AXIS TQ1808-VE is designed to offer room for installation of various Axis accessories and system devices. It's for instance possible to fit AXIS T8504-R Industrial POE Switch and, Power supply DIN PS56 240 W, along with AXIS Electrical Safety kit A 120V AC or kit B 230V AC.

- > **Vandal resistant**
- > **Versatile**
- > **Extended depth**
- > **Designed to fit various Axis accessories and system devices**



AXIS TQ1808-VE Surveillance Cabinet

General		Dimensions	Height: 361 mm (14.2 in) Depth: 229 mm (9 in) Width: 282 mm (11.1 in)
Casing	IP66-, NEMA 4X- and IK10-rated Polycarbonate Stainless steel mounting plate Color: white NCS S 1002-B and stainless steel	Weight	4.1 kg (9.04 lb)
Sustainability	PVC free, BFR/CFR free	Included accessories	Installation guide, Pre-mounted cable gaskets, Pre-mounted DIN rail, Cable clamps, Cable straps, Power cover, Device mounting bracket
Operating conditions	-40 °C to 75 °C (-40 °F to 167 °F) Humidity 10–100% RH (condensing)	Warranty	3-year warranty, see axis.com/warranty
Storage conditions	-40 °C to 75 °C (-40 °F to 167 °F) Humidity 5–95% RH (non-condensing)	Environmental responsibility: axis.com/environmental-responsibility	
Approvals	Safety CAN/CSA C22.2 No. 62368-1 ed.3, IEC/EN/UL 62368-1 ed. 3 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 62262, IEC/EN 60529 IP66, NEMA 250 Type 4X,		