

# AXIS TQ5001-E Wall-and-Pole Mount

## Robust mount for PTZ cameras

With this wall-and-pole mount, installers can choose between using an RJ45 or IDC (insulation-displacement contact) connector for the installation. It features a built-in cable with an Ethernet IP66-rated RJ45 connector to facilitate installation and prevent water and dust from entering the camera. Made from impact-resistant, outdoor-ready material, AXIS TQ5001-E is suited for both indoor and outdoor environments. Flipping the mounting bracket makes it possible to turn AXIS TQ5001-E from a wall mount to a pole mount (AXIS Steel Straps TX30 are required). The mount is also suitable for corner mounting with an optional accessory.

- > **Robust, IK10-rated**
- > **For indoor and outdoor use**
- > **Versatile connection with IDC connector**
- > **Built-in IP66-rated RJ45 connector**
- > **5-year warranty**



# AXIS TQ5001-E Wall-and-Pole Mount

## Approvals

**Product markings** CSA, UL/cUL, UKCA, CE, KC, VCCI, RCM

**Supply chain** TAA compliant

**EMC** CISPR 35, CISPR 32 Class A, EN 55035, EN 55032 Class A, EN 50121-4, EN 61000-6-1, EN 61000-6-2  
**Australia/New Zealand:** RCM AS/NZS CISPR 32 Class A  
**Canada:** ICES-3(A)/NMB-3(A)  
**Japan:** VCCI Class A  
**Korea:** KS C 9835, KS C 9832 Class A  
**USA:** FCC Part 15 Subpart B Class A  
**Railway:** IEC 62236-4

**Safety** CAN/CSA C22.2 No. 62368-1 ed. 3, IEC/EN/UL 62368-1 ed. 3

**Environment** IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-27, IEC/EN 60529 IP66, IEC/EN 62262 IK10, NEMA 250 Type 4X, MIL-STD 810G 509.5

## General

**Supported products** AXIS P55 Series  
 AXIS P56 Series  
 AXIS Q37 Series  
 AXIS Q60 Series  
 AXIS Q61 Series  
 For a complete list of compatible cameras, go to [axis.com/products/axis-tq5001-e-wall-and-pole-mount#compatible-products](https://axis.com/products/axis-tq5001-e-wall-and-pole-mount#compatible-products)

**Casing** IP66-, NEMA 4X- and IK10-rated  
 Aluminum casing  
 Color: white NCS S 1002-B

**Mounting** Back: Cable hole  
 Bottom: 3/4" (M25) conduit side entries

**Connectors** **Output:** IP66, RJ45 Ethernet (male)  
**Input:** RJ45 Ethernet (female), IDC

**Operating conditions** -50 °C to 65 °C (-58 °F to 149 °F)  
 Humidity 10–100% RH (non-condensing)

**Storage conditions** -40 °C to 65 °C (-40 °F to 149 °F)  
 Humidity 10–100% RH (non-condensing)

**Dimensions** For the overall product dimensions, see the dimension drawing in this datasheet.

**Weight** 1960 g (4.3 lb)  
**Maximum load:** 40 kg (88.2 lb)

**Box content** Mount, wall bracket, installation guide, cable ties, RJ45 mounting tool

**Optional accessories** AXIS ACI Conduit Adapters  
 AXIS T91A64 Corner Bracket  
 AXIS Steel Straps TX30 570 mm  
 AXIS Steel Straps TX30 1450 mm  
 For more accessories, go to [axis.com/products](https://axis.com/products)

**Warranty** 5-year warranty, see [axis.com/warranty](https://axis.com/warranty)

**Part numbers** Available at [axis.com/products/axis-tq5001-e-wall-and-pole-mount#part-numbers](https://axis.com/products/axis-tq5001-e-wall-and-pole-mount#part-numbers)

## Sustainability

**Substance control** PVC free

**Materials** Screened for conflict minerals in accordance with OECD guidelines  
 To read more about sustainability at Axis, go to [axis.com/about-axis/sustainability](https://axis.com/about-axis/sustainability)

**Environmental responsibility** [axis.com/environmental-responsibility](https://axis.com/environmental-responsibility)  
 Axis Communications is a signatory of the UN Global Compact, read more at [unglobalcompact.org](https://unglobalcompact.org)

©2022 – 2023 Axis Communications AB. AXIS COMMUNICATIONS, AXIS, ARTPEC and VAPIX are registered trademarks of Axis AB in various jurisdictions. All other trademarks are the property of their respective owners. We reserve the right to introduce modifications without notice.



## AXIS TQ5001-E Wall-and-Pole Mount

|            |      |               |            |
|------------|------|---------------|------------|
| Revision   | v.01 | Revision date | 2023-09-11 |
| Paper size | A4   | Release date  | 2023-09-11 |
| Created by | MS   | Scale         | 1:6        |

© 2023 Axis Communications