

AXIS TQ3601-E Conduit Back Box

IP66/67 rated back box with conduit entrance

Compatible with a wide range of Axis network cameras and especially made for cameras with larger diameters between 184–198 mm (7.2–7.8 in). Available in white, for both outdoor and indoor use this IP66/67 rated back box will withstand challenging outdoor conditions. The back box offers a sealed compartment for secure storage of connectivity devices. 3/4" / M25 conduit interface from both side and back, impact resistant (IK10) and both network cable and extra gaskets are included.

- > **Storage space for cable slack or various system devices**
- > **Impact resistant (IK10) against vandalism attempts**
- > **IP66/67 rated**
- > **Easy installation**
- > **3/4" / M25 conduit interface from both side and back**



AXIS TQ3601-E Conduit Back Box

General		Weight	1.3 kg (2.87 lb)
Supported products	AXIS Q35 Network Camera Series AXIS Q36 Network Camera Series AXIS Q38 Network Camera Series AXIS P38 Network Camera Series	Sustainability	PVC free
Environment	Indoor/outdoor	Approvals	Environment IEC 60068–2–6, IEC 60068–2–27, IEC/EN 60529 IP66/IP67, NEMA 250 Type 4X Impact IEC/EN 62262 IK10
Mounting	Double Gang Box, Single Gang Box, 4" Octagon Junction Box, 4" Square Junction Box	Included accessories	Installation Guide 3x Gasket Tool mounting RJ45 C M20 Cable 3–5 mm 4x Stainless steel screws (TX20) and washers
Casing	Material: powder-coated aluminum casing, stainless steel screws (TX20) Color: white NCS S 1002–B	Optional accessories	AXIS T91B47 Pole Mount, AXIS T94R01B Corner Bracket, AXIS ACI Conduit Adapter 3/4" U-Shape 30 mm, AXIS ACI Conduit Adapter 3/4" NPS, Network cable coupler indoor, Network cable coupler indoor slim, AXIS T6101 Mk II Audio and I/O Interface, AXIS T8645 PoE+ over Coax Compact Kit
Cable routing	Back: 3 cable holes Sides: 3/4" conduit entrances Underside: 4x gaskets C M20 5–9.5 mm Top cover: 3x gaskets C M20 5–9.5 mm	Warranty	3-year warranty, see axis.com/warranty
Maximum load	5 kg (11 lb)		
Dimensions	Height: 53.5 mm (2.11 in) ø 190 mm (7.48 in)		