

AXIS Camera Station S9302 Mk II Workstation

Powerful workstation for flexible installations

Extensively tested and validated with a wide range of Axis products, this powerful and flexible workstation can be used as a client when connected to a server such as AXIS S12 or AXIS S22 Series, or as a server when used in combination with AXIS S30 or AXIS S40 Series. It supports up to four 4K monitors for optimal viewing. With a small form factor, it's ideal wherever space is limited. It comes preloaded with AXIS Camera Station Pro client software. Plus, the integrated AXIS Recorder Toolbox ensures quick and easy installation. Furthermore, it includes next-business-day on-site hardware replacement and a 5-year warranty.

- > **Scalable and powerful solution**
- > **Supports up to four 4K monitors**
- > **AXIS Camera Station Pro client software included**
- > **Extensive support and 5-year warranty**



AXIS Camera Station S9302 Mk II Workstation

Licenses

10 AXIS Audio Manager Pro licenses included and tied to the hardware. Can be upgraded with additional licenses (sold separately).

System scalability

Qualified for 200 simultaneous audio streams using AXIS Audio Manager Pro.

Hardware

Processor

Intel® Core™ Ultra 5 Processor 235

Memory

16 GB (2x 8 GB)

Operating system drive

256 GB SSD

Graphics card

Nvidia® A400

Power

360 W Platinum
(100–240 V AC, 5 A, 50/60 Hz)

Power consumption

Typical: 110 W (375.3 BTU/h)
Maximum: 160 W (545.9 BTU/h)

Connectors

Front side:

1x Universal audio jack
2x USB 2.0
1x USB 3.2 gen 2x2 USB-C
1x USB 3.2 gen 2x1

Rear side:

3x DisplayPort™
1x USB 3.2 gen 2x1 USB-C
3x USB 3.2 gen 1x1
2x USB 2.0
1x 1 GbE RJ45
4x Mini DisplayPort™
1x Power connector

Video

Video streaming

Live view¹:

1 stream x 4K at 30 fps
4 split x 1080p at 30 fps
9 split x 1080p at 30 fps
9 split x 720p at 30 fps
16 split x 450p at 15 fps
25 split x 450p at 15 fps
36 split x 360p at 15 fps
Supports any combination for up to four 4K monitors.

Playback:

High-speed playback may affect video performance.
Playback resolution matches the recording resolution and is not adjusted to the monitor's resolution.

Approvals

Supply chain

TAA compliant

EMC

CNS 15936, EN 55035, EN 55032 Class B,
EN 61000-3-2, EN 61000-3-3,
FCC Part 15 Subpart B Class B, KS C 9835,
KS C 9832 Class B, RCM AS/NZS CISPR 32 Class B,
VCCI Class B

Safety

BSMI, CAN/CSA C22.2 No. 62368-1 ed.3,
IEC/EN 62368-1, KC-Mark, NOM-019,
RCM AS/NZS 62368.1:2022

Environment

EN 50564, EN 62623

Cybersecurity

Edge security

Support for encrypted operating system drive and recording drive
FIPS 140-2 level 2 certified Trusted Platform Module (TPM 2.0)
Secure Boot

Documentation

Axis Vulnerability Management Policy
Axis Security Development Model
Software Bill of Material (SBOM)
To read more about Axis cybersecurity support, go to axis.com/cybersecurity

1. The listed supported configurations have been tested with hardware decoding turned off.

General

Operating system

Microsoft® Windows® 11 IoT Enterprise LTSC 2024
Built-in operating system recovery: yes

Operating conditions

10°C to 35 °C (50°F to 95°F)
Humidity 20–80% RH (non-condensing)

Storage conditions

–40 °C to 65 °C (–40 °F to 149 °F)
Humidity 5–95% RH (non-condensing)

Dimensions

303 x 95 x 293 mm (12 x 3,7 x 11.5 in)

Weight

4.5 kg (9.9 lbs)

Included accessories

4x Mini DisplayPort™ to DisplayPort™ adapters
Wall plug power cord

Optional accessories

Axis joysticks and control boards
For more accessories, see axis.com

Services

Next Business Day onsite support

Warranty

5-year warranty, see axis.com/warranty

Export control

This product is subject to export control regulations, and you should always comply with all applicable national and international export or re-export control regulations.

Sustainability

Substance control

RoHS in accordance with EU RoHS Directive 2011/65/EU, as amended by 2015/863/EU.
REACH in accordance with (EC) No 1907/2006. For SCIP UUID, see echa.europa.eu.

Materials

Post consumer recycled plastics material content used in the product: 39.3%

To read more about sustainability at Axis, go to axis.com/about-axis/sustainability








Environmental responsibility

axis.com/environmental-responsibility

Axis Communications is a signatory of the UN Global Compact, read more at unglobalcompact.org

AXIS Camera Station Pro

For details about AXIS Camera Station Pro features and functions, see the AXIS Camera Station Pro datasheet on *axis.com*



Dimensions in mm [inch]			
Unit	mm	inch	Unit
Width	304	11.95	mm
Height	95	3.74	mm
Depth	293	11.54	mm
Weight	3.485	7.6	kg

AXIS CAMERA STATION S9302 Mk II Workstation



© 2005 Axis Communications AB. All rights reserved.

Highlighted capabilities

SBOM (Software Bill of Materials)

SBOM is a detailed list of all software components included in an Axis product, including third-party libraries and license information. This list provides customers with insight into the product's software composition, facilitating the management of software security and meeting transparency requirements.

TPM (Trusted Platform Module)

TPM is a security chip integrated into Axis devices to provide a secure environment for storing and processing sensitive data. As a component providing a set of cryptographic features, the TPM protects information from unauthorized access. Specifically, it securely stores the private key, which never leaves the TPM, and processes all related cryptographic operations within the module itself. This ensures the secret part of the certificate remains safe even in the event of a security breach. By enabling features like encryption, authentication, and platform integrity, the TPM contributes to safeguarding the device against unauthorized access and tampering.

Secure Boot

Secure Boot is a security system that ensures only approved software (operating system and embedded switch firmware when applicable) runs on an Axis device at startup. It uses a boot process consisting of an unbroken chain of cryptographically validated software, starting in immutable memory (boot ROM), to verify the authenticity of the software. By establishing the trust chain, Secure Boot guarantees that the device only executes software with a valid digital signature, preventing malicious code from running on the device and ensuring the device boots only with a signed software.

For more information, see [axis.com/glossary](https://www.axis.com/glossary)