



Televes reserves the right to modify the product

Pre-terminated optical fibre patch cord

Outdoor FC/PC

Single-mode (SM) optical-fibre patch cord Pre-terminated with FC/PC connectors for the connection of network elements, usually of the optical LNB range. Equipped with a shielded stainless steel tube covering the fibre as well as a traction protective aramid mesh (kevlar) and an LSFH ultraviolet radiation-resistant sheath. It can therefore be used outdoors and even under ground. Supplied in individual packing.

Ref.2361	3 m	
	Art.Nr	OSK3S
	EAN13	8424450142752
Ref.236101	5 m	
	Art.Nr	OSK5S
	EAN13	8424450142769
Ref.236102	10 m	
	Art.Nr	OSK10S
	EAN13	8424450142776
Ref.236103	20 m	
	Art.Nr	OSK20S
	EAN13	8424450142783
Ref.236104	30 m	
	Art.Nr	OSK30S
	EAN13	8424450142790
Ref.236105	40 m	
	Art.Nr	OSK40S
	EAN13	8424450142806
Ref.236106	50 m	
	Art.Nr	OSK50S
	EAN13	8424450142813
Ref.236107	75 m	
	Art.Nr	OSK75S
	EAN13	8424450142820

Ref.236108	100 m	
	Art.Nr	OSK100S
	EAN13	8424450142837
Ref.236109	200 m	
	Art.Nr	OSK200S
	EAN13	8424450142844
Ref.236110	1 m	
	Art.Nr	OSK1S
	EAN13	8424450186541

Highlights

- Low attenuation
- Kevlar protection and flexible stainless steel tube

Main features

- G.657A2 fibre type
- LSFH cover with UV protection, grey colour
- FC/PC connectors
- Available in different lengths

Specifications

Technical specifications		
Fiber	Type	Monomode
Optics connectors	Type	FC/PC
Cover material	Type	LSFH
Attenuation	dB	≤ 0,3
Insertion losses	dB	≤ 0,2
Return losses (in each patch cord)	dB	≥ 45
Minimum radius of curvature	mm	30
Outside diameter of the fiber	mm	3