

Power Cutter LXT®

DCE090

2 x 18 V • 230 mm • 6 600 min⁻¹

Powerful Power Cutter LXT® for heavy duty use.

Water supply kit can be connected; The hose is designed to run inside the tool housing to prevent from being caught in objects. Active Feedback sensing Technology (AFT) turns the motor off if rotation speed suddenly slows or wheel is forced to stop.



Technical specifications

Nominal Battery Voltage	2 x 18 V
Voltage LXT	✓
Brushless Motor	✓
No load speed	6600 min ⁻¹
Blade Diameter	230 x 22,23 mm
Max. Depth of Cut	88 mm
Dead Man's Switch (No Lock-On)	✓
Electronic brake	✓
Sound Power Level (L _{WA})	114 dB(A)
Sound Pressure Level (L _{pA})	103 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Uncertainty (K Factor)	1,5 m/s ²
Tool weight with battery (EPTA)	5,6 - 6,3 kg
Product Dimensions (L x W x H):	554 x 241 x 283 mm
Product net weight	4,9 kg

User benefits

- Battery protection system automatically shuts off power when the battery level is low

Link to product - www.makita.uk.com



Related products

Optional AC

B-12712

Diamond wheel 230 mm, Quasar



B-54025

Diamond wheel 230 mm, Nebula, Dry



BL1820B

Battery LXT® 2,0 Ah



BL1830B

Battery LXT® 3,0 Ah



BL1840B

Battery LXT® 4,0 Ah



BL1850B

Battery LXT® 5,0 Ah



BL1860B

Battery LXT® 6,0 Ah



Other

User manual

Parts drawing