



FSP ADVAN GM 1000W Power supply unit ATX ATX3.1 Black

Brand : FSP

Product code: PPA10A4200

Product name : ADVAN GM 1000W Power supply unit ATX ATX3.1 Black

- Efficiency $\geq$ 90% at typical load
- 80 PLUS® gold certified
- 105°C Japanese bulk capacitor
- 120mm hydraulic bearing (HYB) fan
- Eco semi-fanless fan control switch
- Premium, black embossed cables for easier cable routing
- Complete protections: OVP, OCP, OPP, OTP, SCP, UVP, SIP, NLO

ADVAN GM 1000W

FSP ADVAN GM 1000W Power supply unit ATX ATX3.1 Black. Total power: 1000 W, AC input voltage: 100 - 240 V, Input current: 6 A. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 60 cm, PCI Express power cable length: 70 cm. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Gold. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Width: 150 mm, Depth: 140 mm, Height: 86 mm



Power		Ports & interfaces	
Total power *	1000 W	PCI Express power connectors (6+2 pin)	2
AC input voltage *	100 - 240 V	PCI Express power connectors (12-pin)	1
Input current	6 A	PCI Express power cable length	70 cm
Power factor	0.9	CPU power connector (4+4 pin)	✓
Power Factor Correction (PFC) type	Active	CPU power cable length	70 cm
Combined power (+3.3V)	100 W	Cabling type	Fully-Modular
Combined power (+12V)	1000 W	Performance	
Combined power (+5V)	100 W	80 PLUS certification *	80 PLUS Gold
Combined power (-12V)	3.6 W	Purpose *	PC
Combined power (+5Vsb)	15 W	Power supply unit (PSU) form factor *	ATX
Max output current (+3.3V)	20 A	ATX version	3.1
Max output current (+12V)	83.33 A	Bearing technology	HYB
Max output current (+5V)	20 A	Design	
Max output current (-12V)	0.3 A	Product colour	Black
Max output current (+5Vsb)	3 A	Cooling type	Active
Efficiency	90%	Fan diameter	12 cm
Power protection features	No load operation, Over current, Over power, Over voltage, Short circuit, Surge & inrush protection (SIP), Under voltage	Number of fans	1 fan(s)
		On/off switch	✓
Ports & interfaces		Weight & dimensions	
Motherboard power connector *	20+4 pin ATX	Width	150 mm
Motherboard power cable length	60 cm	Depth	140 mm
Number of SATA power connectors	4	Height	86 mm
Peripheral (Molex) power connectors (4-pin) *	4		



4711498480798

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.