

Techly IDATA HDMI-KVM67 KVM extender Transmitter & receiver

Brand : Techly

Product code: IDATA HDMI-KVM67

Product name : IDATA HDMI-KVM67

- HDMI KVM Extender with transmitter and receiver
 - Allows extending HDMI signal up to 70 meters via a single network cable with zero latency
 - Supports audio formats (Dolby True HD 7.1CH, Dolby Digital 5.1CH)
 - Supports resolution up to 4K@60Hz, HDR (YUV4:4:4), EDID passback
 - Receiver can extract digital audio from transmitter through S/PDIF port
 - Support KVM function
 - Transmitter supports HDMI loop-out
 - With Lightning protection, surge protection and ESD protection
- HDMI KVM Extender Over Network Cable 4K@60Hz 70 m

Techly IDATA HDMI-KVM67 KVM extender Transmitter & receiver:

This HDMI extender include a trnsmitter unit and a receiver unit, allows HDMI signal to be transmitted up to 70 meters at 4K resolution using a CAT6/6A/7 network cable. It is perfect for outdoor advertising, video clips, monitor system, home entertainment, and conference, etc.



Features		Power	
Type *	Transmitter & receiver	AC adapter output voltage	5 - 12 V
Connectivity technology *	Wired	Power consumption (transmitter) (max)	4 W
Maximum transfer distance	70 m	Power consumption (receiver) (max)	4 W
Cable types supported	Cat6, Cat6a, Cat7	Weight & dimensions	
Maximum digital resolution	4096 x 2160 pixels	Transmitter width	15 cm
Maximum refresh rate	60 Hz	Transmitter depth	10.7 cm
Audio support	✓	Transmitter height	2.84 cm
Product colour	Black	Transmitter weight	1.45 kg
Certification	CE, FCC	Receiver width	15 cm
Transmitter		Receiver depth	10.7 cm
Transmitter video port type	HDMI	Receiver height	2.84 cm
Transmitter local keyboard/mouse port type	USB	Receiver weight	1.45 kg
RJ-45 ports quantity (transmitter)	1	Packaging content	
Receiver		AC adapter included	✓
Receiver local video port type	HDMI	Screwdriver included	✓
Receiver local keyboard/mouse port type	USB	Cables included	USB
RJ-45 ports quantity (receiver)	1	Manual	✓
Ports & interfaces		Mounting bracket(s) included	✓
USB port type	USB Type-A	Operational conditions	
HDMI version	2.0	Operating temperature (T-T)	-20 - 60 °C
		Storage temperature (T-T)	-30 - 70 °C
		Operating relative humidity (H-H)	0 - 90%
		Other features	
		Compliance certificates	CE



8059018361629

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.