



Lindy 0.5m CAT6 S/FTP Network Cable, Grey

Brand : Lindy

Product code: 47701

Product name : 0.5m CAT6 S/FTP Network Cable, Grey

0.5m Cat.6 S/FTP Network Cable, Grey

Lindy 0.5m CAT6 S/FTP Network Cable, Grey:

Cat.6 S/FTP network cable with support for bandwidth up to 250MHz and features a snagless design with gold plated contacts for ethernet standards up to 1GBase-T.

Cat.6 cable for operating frequencies up to 250MHz in shielded version with braid as overall shield and foil shield for the individual wire pairs (S/FTP). Cat.6 cables are widespread throughout the professional sector. They are ideal for Gigabit Ethernet or AV extension applications. These cables are manufactured and tested according to the ISO/IEC 11801 specification. The cables are packaged individually in a polybag.

The gold-plated contacts ensure reliable, corrosion-free connections over extensive periods of time. A robust snagless strain relief design prevents damage to the connector latch during installation and removal.

Available lengths: 0.3m, 0.5m, 1m, 1.5m, 2m, 3m, 5m, 7.5m, 10m, 15m, 20m, 30m.

Available colours: Blue, Red, Green, Yellow, Black, White, Orange, Purple, Grey.



Features		Features	
Product colour *	Grey	Frequency	250 MHz
Cable length *	0.5 m	Bend radius (min)	7.4 cm
Cable standard *	Cat6	Snagless cable boot	✓
Cable shielding *	S/FTP (S-STP)	Operational conditions	
Connector 1 *	RJ-45	Operating temperature (T-T)	-10 - 60 °C
Connector 2 *	RJ-45	Storage temperature (T-T)	-20 - 75 °C
Connector 1 gender *	Male	Certificates	
Connector 2 gender *	Male	Certification	RoHS, REACH, UL, California Proposition 65
Connector contacts plating	Nickel/Gold	Weight & dimensions	
Connector shielding	✓	Outer diameter	6.2 mm
Connector shield material	Aluminium	Connector 1 dimensions (WxDxH)	11.6 x 22.8 x 8.3 mm
Jacket material	Polyvinyl chloride (PVC)	Connector 2 dimensions (WxDxH)	11.6 x 22.8 x 8.3 mm
Conductor material	Copper	Packaging data	
Cable class	E	Package type	Polybag
Cabling technology	10/100/1000Base-T(X)	Logistics data	
AWG wire size	27	Harmonized System (HS) code	84733080
Data transfer rate	1000 Mbit/s		



4002888477017

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.